

# CTP-V15HD

960H INDOOR DOME CAMERA

CANTEK+

## FUNCTION

- 1/3" 960H IT CCD
- HIGH RESOLUTION 700TV Line
- 2.8~12mm DC AUTO IRIS LENS
- BUILT-IN OSD CONTROLLER & 2nd BNC CONNECTOR
- 3DNR (DIGITAL NOISE REDUCTION)



## SPECIFICATION

| DESCRIPTION            | NTSC  | PAL               |
|------------------------|---|-------------------|
| IMAGE SENSOR           | 1/3" 960H IT CCD                            |                   |
| EFFECTIVE PIXEL        | 976(H) x 494(V)                             | 976(H) x 582(V)   |
| SCANNING SYSTEM        | 2:1 Interlace                               |                   |
| SYNCHRONIZATION        | Internal                                    |                   |
| HORIZONTAL RESOLUTION  | 700TV Lines                                 |                   |
| VIDEO OUTPUT           | COMPOSITE (1.0Vp-p/75Ohm)                   |                   |
| S/N (Y Signal)         | 52dB (AGC off)                              |                   |
| LENS                   | 2.8~12mm DC IRIS VARIFOCAL LENS             |                   |
| ELECTRONIC SHUTTER     | 1/60 ~ 120,000sec                           | 1/50 ~ 120,000sec |
| BACKLIGHT COMPENSATION | BLC / HSBLC / OFF                           |                   |
| WHITE BALANCE          | JSH / USER1 / USER2 / ANTI CR / MANUAL / PU |                   |
| DAY & NIGHT            | COLOR / AUTO / B/W / EXT1 / EXT2            |                   |
| PRIVACY MASKING        | ON/OFF (8 zones)                            |                   |
| DNR                    | OFF / LOW / MIDDLE / HIGH                   |                   |
| SMART IR               | OFF / ON                                    |                   |
| SENS UP                | OFF / x1 ~ x512                             |                   |
| MOTION                 | OFF / ON (4 POINTS)                         |                   |
| DEFECT DET             | OFF / ON                                    |                   |
| IR LED                 | —   |                   |
| INPUT VOLTAGE          | DC 12V(±10%)                                |                   |
| POWER CONSUMPTION      | 130mA(±10%)                                 |                   |
| OPERATING TEMP. / HUM. | -10°C ~ +50°C / MAX 90% RH                  |                   |
| STORAGE TEMP. / HUM.   | -20°C ~ +60°C / MAX 90% RH                  |                   |

## DIMENSION Unit : mm

