



3 axis joysticks for PTZ control

- USB 1.1 HID compliant controller
- Programmable pushbutton switches
- · Easy to use and operate
- Compatible with ACTi's video management system

DIMENSION DIAGRAM





Unit: mm (inch)

Joystick

PRODUCT SPECIFICATION

	PJSK-0100
Device	
Joystick Performance	Hall effect three axis joystick; X/Y/Z for positioning control
Joystick Travel	36° for X and Y axis; 60° f or Z axis
Centering	Single spring, omni-directional
Pushbutton Performance	10 tactile pushbuttons on housing; Two tactile pushbuttons on joystick; 3,000,000 cycles
Connectors	USB Type A Male; Cable Length: 2m (6.8")
Supported Protocols	USB HID 1.1 controller; Direct X; Joystick: Three HID axes; Pushbuttons: 12 HID buttons; Standard DirectX HID drivers
General	
Joystick Shaft Material	Stainless steel
Joystick Boot Material	Neoprene
Joystick Handle Material	Glass filled nylon
Desktop Housing	High impact ABS housing
Power	Via USB interface (5V DC); Consumption 32mA
Operating Temperature	-25°C ~ 85°C (-13°F ~ 185°F)
Approvals	EN 55024:1998, EN 55022, CE; FCC Part 15 Subpart B Class B; RoHs compliant
Weight	440 g (0.97lb)
Supported Operating Systems	Windows 7, Vista, Windows XP, Windows 2000, Window 8, OSX, Linux
Application Environment	Indoor use only
 Integration 	
Unified Solution	Fully compatible with ACTI's video management system