

Sensors

35ft Reflective Photobeam Sensor

E-931-S35RRQ Range: Up to 35ft (11m)

Features:


- For outdoors gates, garage doors, etc.
- Adjustable sensing range
- 12~240VDC / 24~240VAC Operation
- Current: Up to 40mA@12VDC
- For indoor or outdoor use (IP66)
- Pre-wired 6ft (1.8m) cord
- Brackets and mounting hardware included
- Compact size
- New single-gang box and wall-mount brackets available

Specifications:

Model	E-931-S35RRQ
Туре	Retro-reflective
Sensing range	0.5'~35' (0.2~11 m)
Voltage supply	12~240 VAC/VDC
Current draw	40mA@12VDC
Response time	10ms (max)
Light source	IR LED
LEDs	Yellow LED (standby)
	Red LED (trigger)
Trigger output	SPDT relay output (NO/NC/COM)
Switching capacity	1A@120VAC / 2A@30VDC
Enclosure	IP66 weatherproof
Ambient temperature	-4°~131° F (-20°~55° C)
Mounting brackets	Included

Dimensions:

Reflector





Sensor ¹³/₁₆" 1⁵/8" (40mm) (20mm) 00 п 25/16" 2⁵/8" (66mm) (58mm) 0 1³/₁₆' (30mm) Ø ³/₁₆" (4.5mm) Ø 1/4" (6mm) 1/4 cable 6.5' (2m) (6mm)

Optional Accessories:

E-931ACC-RC1Q 3" Round reflector

E-931ACC-HR1Q Reflector hood









SECO-LARM® U.S.A., Inc. 16842 Millikan Avenue, Irvine, CA 92606 Phone: (949) 261 2999 L (800) 662 0800 Eax: (0

 Phone:
 (949)
 261-2999
 (800)
 662-0800
 Fax:
 (949)
 261-7326

 Website:
 www.seco-larm.com
 Email:
 sales@seco-larm.com
 SE

Copyright 2014 © SECO-LARM U.S.A., Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM° **ENFORCER**° CRIWEBUSTER° CBA *SLI "E*

PiE-931-S35RRQ_141015.docx