SECO-LARM®

Electric Door Strike

SD-994CFor wood doors, 12VDCSD-994C24For wood doors, 24VDC

The **SECO-LARM** Electric Door Strike can be used to convert cylindrical lock sets into an electronic access-controlled locking system. Combine with an optional digital keypad such as the **SECO-LARM[®]** *SK-1131-SPQ* for keyless high security.

Features:

- Field-programmable in just seconds for fail-safe or fail-secure applications
- Can be used with virtually any cylindrical door locking system
- Use with an optional digital keypad
- Suitable for office-type applications
- Symmetrical-sized, reversible for right-hand or left-hand doors
- Shallow design for use with most wood doors
- Powered by a solenoid, not a buzzer coil
- Jaw strength 2,000 lbs
- Stainless-steel lip (keeper) for strength and long life
- Non-polarized connection; wires can be reversed
- Tested to 1 million cycles
- Includes trim plate to hide gaps in installation
- Optional lip-extension brackets available:



- SD-995C-LE25 1" Extension
- SD-995C-LE50 2" Extension

SD-995C-LE25 shown

Specifications:

Model #	SD-994C	SD-994C24
Operating voltage	12VDC	24VDC
Current draw	250mA	150mA
Operating temperature	14°~113°F (-10°~45° C)	
Jaw strength	2,000-lb	
Dimensions	7 ¹⁵ / ₁₆ "x1 ⁷ / ₁₆ "x1 ¹ / ₄ "	
	(202x36x32 mm)	

SECO-LARM[®] U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606 Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: www.seco-larm.com Email: sales@seco-larm.com

Access



Also Available from **SECO-LARM**[®]:



SD-995C SD-995C24 Electric Door Strike for Metal Doors



SD-996C-NUQ Universal Door Strike



Copyright 2015 © SECO-LARM U.S.A., Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® **Enforcer**® CrimeBuster® CBA *SLI*

PiSD-994C_151006.docx