

### 2-Channel RF Transmitters and Receiver

**SK-919TD2A-UP** 2-Button Pre-Coded Transmitter

**SK-917T2A-UQ** 2-Button CODEBUMP™ Transmitter

- Range: Up to 500ft (152m)\*, 315MHz
- LED Transmission indicator
- Includes 12VDC alkaline battery
- Compatible with all 315MHz SECO-LARM receivers
- SK-919TD2A-UP: 68 billion possible codes
- SK-917T2A-UQ: 18 quintillion possible codes



SK-919TD2A-UP



SK-919TP2H-NUQ

**SK-919TP2H-NUQ** 2-Button Handheld Transmitter

- Range: Up to 500ft (152m)\*, 315MHz
- Over 68 billion possible codes
- Includes two 3VDC lithium batteries
- Compatible with all 315MHz SECO-LARM receivers
- Visor clip and belt clip included. Belt-clip holster and wall-mount bracket also available (model #: SK-9HBC)
- Low battery indicator – LED flashes when battery drops below 2VDC




SK-910RB2Q

**SK-910RB2Q** 2-Channel Receiver

- Five programmable relay output modes:
  - 4-Second momentary
  - 1-Second momentary
  - Toggle (ON/OFF)
  - Latch
  - Validity
- 11-24 VAC/VDC Operation
- Range: Up to 500ft (152m)\*, 315MHz
- Independently programmable outputs
- Controls garage doors, gates, house lights, alarm panels or other devices via remote
- Two LEDs indicate RF reception, learn mode entered, transmitter learned, memory cleared, and relay output mode
- Pushbutton programming, no need to cut jumpers
- Up to 15 transmitter button codes per channel can be learned
- Compatible with all 315MHz SECO-LARM transmitters

\*Actual range will vary greatly depending on the installation and operating environment

Also Available from **SECO-LARM®**:

<b>SK-91ERSD</b>	
Increase range up to 1,000ft (304m)* with the Extended Range Antenna	

#### SK-910RB2Q Specifications:

Operating frequency	315MHz	
Memory capacity	15 Transmitter button codes per channel, 30 total	
Operating voltage	11-24 VAC/VDC	
Operating current	Standby	8mA@12VDC
	Active	30mA@12VDC
Relay output modes	4-Sec momentary, 1-sec momentary, toggle, latch, validity	
Relay contact rating	Form C 10A@24VDC/120VAC	
Connectors	Screw terminals: Power (+,-) 1 relay per channel (NO/NC/COM)	
Dimensions	3 1/16" x 3 1/16" x 1 1/8" (87x87x28 mm)	