

MNR-310



Model	MNR-310
Product Type	Standalone NVR
Maximum Number of Video devices	32
Processor	Intel Atom D2550
Maximum Number of Clients	1 local, 3 remote
License required	Yes
Free License	16 (16-channel for ACTi and 1-channel for third-party video device)
Video Resolution	Support all ACTi cameras in all resolutions
Compression	H.264, MPEG-4, MJPEG
Audio	2-way
Network Connector	RJ-45
Wireless	Yes (Wi-Fi, 4G, GPS need optional accessories)
Serial Port	RS-232
Power Source	AC 100-240V; DC 12V(9-36V)
Built-in Analytics	Motion Detection, Tamper
Scheduled Recording	Yes
Event Recording	Yes
Manual Recording	Yes
Speed Up	Yes
Dual Stream Management	Yes
Recording Throughput	192 Mbps
HDD Interface	Maximum 2 SATA disks
External Storage Interface	eSATA, iSCSI, USB
RAID Level	Software RAID 0, 1
Display Layout Mode	Local: 1, 2, 4
Local Live View performance	Please check "Standalone NVR Performance Validator" ( <a href="http://www.acti.com/SANVRPerformance">http://www.acti.com/SANVRPerformance</a> )
Digital Zoom	Yes
Event Status	Display event status upon alarm or upon connection loss or recovery between server and client or when the allocated disk space is full
Instant Playback	Instant Playback in live view window (Remote client)
e-Map	Yes
PTZ Control	Yes
Playback Control	Continuous forward and backward playback with speeds 1x/2x/4x/8x/16x or frame-by-frame; pause; stop
Synchronized Playback	4 channels (local), 32 channels (remote)
Local Access	HDMI/VGA monitor; USB keyboard & mouse; USB joystick
Remote Access	Workstation, Web Client (IE), Mobile Client (iOS & Android)
Event Trigger	NVR: Disk full; Disk not found; Disk is available;  Device: Video motion detection; Passive IR sensor; External device through digital input; Video loss and recovery; Network loss and recovery
Event Response	Pop-up window with live video; Switch to hotspot window; Switch to customize View; Command a PTZ device to go to a preset point; Play alert sound; Activate external device through digital output; Execute system command to activate other programs; Upload snapshot to FTP server; E-mail notification with snapshots
Permission Control	Unlimited number of users and user groups, Active Directory, Customizable permissions for user groups, Playback Password protected, Password Validity Period
GPS Position	Manual setting
Video Export	eSATA, USB
Video Export Formats	RAW, AVI, EXE
Server Operating System	Embedded Windows 7
Client PC Operating System	Windows 10, Windows 8, Windows 7, Windows Server 2012, Windows Server 2008
PC Web Browser	IE 10, IE 11
Unified Solution	Fully compatible with ACTi cameras, encoders, central management system, TV wall and intelligent video surveillance software
ONVIF Compliant	Yes (Profile S)
Packing Dimension	35 x 35 x 26 (cm)
Operating Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Warranty	2 Years
Approvals	CE, FCC, e-Mark, UL (for built-in power adapter)
Product Availability	ACTi : Now Distributor : Now