DATA SHEET

COD. 3208HXV

8 BUTTON FLUSH 316 ANALOG A/V PANEL VIP

Flush-mounted entrance panel (fitted level with the wall) and plate in 3mm thick stainless steel; buttons integrated into the plate, with no mechanical movement. IK08 certification. Nameplates with LED lighting and front access for name replacement. Allows management of visual call, conversation and door lock status indications. Complete with a/v ViP unit Art. 4682HC for audio/video/door lock management, and flush-mounted box with concealed fixing screws. For powering at 33Vdc with Art. 1595. Dimensions 408x182x3 mm. Compatible with H264 video format.

General specifications

Signal/noise ratio (dB):	48
Video output:	1 Vpp / 75 PAL

Software/firmware specifications

Video resolution (H x V):	500x582
No. of storable users:	8

Hardware specifications

Vandal Resistant IK:	IK08
DDE function:	Yes
Total buttons:	8
Sensitive Touch technology:	Yes

Functions

Key button function:	Yes
Loudspeaker volume control:	Yes

General info

Product height (mm):	408
Product width (mm):	182
Product depth (mm):	60
Operating temperature (°C):	-25/55
S/N ratio dB:	48

Compatibility

Video door entry family:	Yes

The technical specifications are subject to variations without warning

Vip system:	Yes

Mounting/Installation

Flush-mounted:	Yes

Audio/video specifications

Audio/video system:	Yes

Connectivity

Ethernet ports:	1

Technical properties

Sensitivity (lux):	1,0 msx AGC, 50% video out
Type of camera:	COLOR

Electrical specifications

Maximum current absorption (mA):	450

The technical specifications are subject to variations without warning