

MDJ700/710/720
MDJ701/711/721 & MDJ760



MODELS

Dedicated Models:

Display adaptor purchased separately*




MDJ700	In-line Display	Black
MDJ710	In-line Display	Black
MDJ720	In-line Display	Black
MDJ701	Curvilinear Display	Black
MDJ711	Curvilinear Display	Black
MDJ721	Curvilinear Display	Black
MDJ760	Circular Display	Black

* Dedicated adaptor plates come in flat black and include security fasteners

DISPLAY ADAPTOR

Dedicated Models: Requires display-specific adaptor to be purchased separately.





SPECIFICATIONS

	Distance from Ceiling	1'-12' (305-3658mm) Varies depending on ceiling plate and extension column used
	Tilt Swivel	+20° 360°
	Max Load	600-1200lb (272-545kg) Depending on ceiling attachments used
	Product Dimensions (Pipe Length)	
	MDJ700/701:	120" (3048mm)
	MDJ710/711:	180" (4572mm)
	MDJ720/721:	240" (6096mm)
	MDJ760:	48" (1220mm)

CERTIFICATIONS



ACCESSORIES

	PLCM-4: Stackable Base Mount for up to 75" Displayspg# 89
	PLP-UNM: Universal Adaptor Bracket for 22" to 46" Displayspg# 89, 228
	PLP-UNL: Universal Adaptor Bracket for 32" to 75" Displayspg# 89, 228
	PLP-V models: Dedicated Adaptor Plates ..pg# 89, 228


Multi-Display Ceiling System

FOR 32" TO 50" DISPLAYS

1. Multi-Display ceiling mount for 3 to 4 displays
2. Three different configurations: in-line, curvilinear, and circular
3. Choose desired ceiling drop length and drop length of equipment from pipe
4. 0° to 20° adjustable tilt
5. 360° swivel for each display



Circular configuration



In-line configuration



Curvilinear configuration

Required Components



WARRANTY: Limited 5-year

CIRCULAR								
Display Size	Number of displays	MDJ model*	PLCM-2 display mount	PLP display adaptor plate (see MountFinder™)	EXT or AEC extension column (connects PLCM-2 to ACC600)	ACC600 interface bracket to MDJ mount	ADD* support extension column	DCT ceiling decoupler
32"-37"	3	MDJ760	3	3	3	3	1	1
40"-42"	3	MDJ760	3	3	3	3	1	1
50"	3	MDJ760	3	3	3	3	1	1
32"-37"	4	MDJ760	4	4	4	4	1	1
40"-42"	4	MDJ760	4	4	4	4	1	1


* Columns over 9' will be covered in vinyl

IN-LINE								
Display Size	Number of displays	MDJ model	PLCM-2 display mount	PLP display adaptor plate (see MountFinder™)	EXT or AEC extension column (connects PLCM-2 to ACC600)	ACC600 interface bracket to MDJ mount	ADD support extension column	DCT ceiling decoupler
32"-37"	3	MDJ700	3	3	3	5	2	2
40"-42"	3	MDJ700	3	3	3	5	2	2
50"	3	MDJ710	3	3	3	5	2	2
32"-37"	4	MDJ700	4	4	4	6	2	2
40"-42"	4	MDJ710	4	4	4	6	2	2
50"	4	MDJ720	4	4	4	7	3	3

CURVILINEAR								
Display Size	Number of displays	MDJ model	PLCM-2 display mount	PLP display adaptor plate (see MountFinder™)	EXT or AEC extension column (connects PLCM-2 to ACC600)	ACC600 interface bracket to MDJ mount	ADD support extension column	DCT ceiling decoupler
32"-37"	3	MDJ701	3	3	3	5	2	2
40"-42"	3	MDJ701	3	3	3	5	2	2
50"	3	MDJ711	3	3	3	5	2	2
32"-37"	4	MDJ701	4	4	4	6	2	2
40"-42"	4	MDJ711	4	4	4	6	2	2
50"	4	MDJ721	4	4	4	7	3	3

MULTI-DISPLAY SYSTEM COMPONENTS							
Multi-Display Mount	Model	Length	Ring Diameter	Pipe Diameter	Load Capacity	Ship Weight	
 In-line Curvilinear	 Circular	MDJ700 (in-line)	120" (3048mm)	NA	1.90" OD	1000lb (453kg)	31lb (14.1kg)
		MDJ710 (in-line)	180" (4572mm)	NA	1.90" OD	1200lb (544kg)	45lb (20.4kg)
		MDJ720 (in-line)	240" (6096mm)	NA	1.90" OD	1500lb (680kg)	62lb (28.1kg)
		MDJ701 (curved)	120" (3048mm)	NA	1.90" OD	1000lb (453kg)	27lb (12.2kg)
		MDJ711 (curved)	180" (4572mm)	NA	1.90" OD	1200lb (544kg)	35lb (15.9kg)
		MDJ721 (curved)	240" (6096mm)	NA	1.90" OD	1500lb (680kg)	56lb (25.4kg)
		MDJ760 (circular)	NA	48" (1219mm)	1.90" OD	600lb (272kg)	45lb (20.4kg)

Display Mount	Model	Ship Weight
	PLCM-2 PLP display adaptor required. See MountFinder™ to verify display compatibility.	6.9lb (3.1kg)


Multi-Display Interface Bracket	Model	Description	Load Capacity	Ship Weight
	ACC600	Interfaces between flat panel mount to MDJ mount, and MDJ mount to ceiling support structure.	1200lb (544kg)	3.8lb (1.7kg)

Fixed or Adjustable Extension Columns for Attaching Mount	Model	Drop Length*
	EXT/AEC models	6"-12' (152-3657mm)

* Fixed length columns provide 6" to 10' (152.4-3048mm) drop lengths. Adjustable length columns provide 6" to 12' (152-3657mm) drop lengths.

Fixed or Adjustable Extension Columns for Ceiling Decouplers	Model	Drop Length*
	ADD models	1'-12' (304-3657mm)

* Fixed length columns provide 1' to 10' (304-3048mm) drop lengths. Adjustable length columns provide 1' to 12' (304-3657mm) drop lengths.

Ceiling Decoupler	Model	Ceiling type	Load Capacity	Ship Weight
 DCS400 DCT300 DCT500-900	DCS400	For structural or finished ceiling	1200lb (544kg)	7.8lb (3.5kg)
	DCT300	For truss ceiling	1200lb (544kg)	4.6lb (2.1kg)
	DCT500	For I-Beams	600lb (272kg)	9.4lb (4.3kg)
	DCT600	For I-Beams	600lb (272kg)	13.1lb (6kg)
	DCT700	For I-Beams	600lb (272kg)	13.6lb (6.2kg)
	DCT800	For I-Beams	600lb (272kg)	14lb (6.4kg)
	DCT900	For I-Beams	600lb (272kg)	9lb (4.1kg)

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV
2300 White Oak Circle
Aurora, IL 60502 USA

(800) 865-2112
(630) 375-5100
Fax: (800) 359-6500

Peerless-AV Europe
Unit 3 Watford Interchange
Colonial Way, Watford
Herts, WD24 4WP
United Kingdom
+44 (0) 1923 200100
Fax: +44 (0) 1923 200101

Peerless-AV de México
Ave de las Industrias 413
Parque Industrial Escobedo
Escobedo, N.L.,
Mexico 66050
+52 (81) 8384-8300
Fax: +52 (81) 8384-8360

