# LC-LC 50/125µm OM2 MM Duplex Fiber Optic Jumper



## **Package Includes**

- A. LC-LC 50/125µm OM2 MM Duplex Fiber Jumper, 1 pc.
- B. Test Results Label, 1 pc.


### **Features and Benefits**

- Made from OFNR riser rated cables, exceeding all industry requirements Used with ICC fiber optic products
  Available in 1, 2, 3, 5, 7, and 10 meters
  Dust caps included

- Test results included







#### NOTE: UNLESS OTHERWISE SPECIFIED

#### 1. Cable:

A. Color: Orange

B. Fiber Counts: 2 Fiber Zipcord

C. Fiber Type: Multimode 50/125µm

D. Attenuation: 2.3/0.6 dB/km @ 850/1300 nm E. Bandwidth: 950 MHz.km EMB @ 850 nm

F. Cable Data:

• Cable diameter: .079 in (2.0mm)

Weight: 12 lbs./kftBend radius: 1.2" MIN

• Loading: 135 lbs. MAX

Impact cycle: 1500

#### 2. LC Connector:

A. Ferrule: Zirconia

B. Insertion Loss: 0.2 dB Typical, 0.3 dB MAX

C. Reflection: N/A

#### 3. Compliance:

A. ANSI/TIA-568-C.3

4. Length: XX: 01, 02, 03, 05, 07, & 10

ITEM NUMBER	L (LENGTH)
ICFOJ1M701	1 METER ± 10 CM
ICFOJ1M702	2 METER ± 10 CM
ICFOJ1M703	3 METER ± 10 CM
ICFOJ1M705	5 METER ± 10 CM
ICFOJ1M707	7 METER ± 10 CM
ICFOJ1M710	10 METER ± 10 CM

Part No: ICFOJ1M7XX

Rev: A Page 2 of 2 I 888-ASK-4ICC icc.com csr@icc.com

