



# R615DC616ULCB DC Rack Mount CCTV Power Supply

Rev. R615DC616ULCB\_10202014



R615DC616ULCB

## **Overview**

R615DC616ULCB provides 6-15VDC distributed via sixteen (16) PTC protected outputs for powering CCTV cameras, heaters and other video accessories.

## **Specifications**

### ***Input:***

- 115VAC, 50/60Hz, 1.5 amp.

### ***Output:***

- Sixteen (16) Class 2 Rated PTC protected outputs.
- 6-15VDC @ 6 amp total output current.  
(0.375 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.

### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 18.43 - 46.06 BTU/Hr.
- System AC input VA requirement: 172.5VA.

### ***Features:***

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.

### ***Mechanical:***

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.):  
3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
- Product weight (approx.): 17.15 lbs. (7.78 kg).
- Shipping weight (approx.): 18.15 lbs. (8.23 kg).

## **Agency Approvals**



UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.

**Enclosure Dimensions (H x W x D approximate):**  
 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)

