



VB6

Overview

Altronix VB6 is a cost-effective 56VDC/30W UL Listed limited power supply. It is intended to power PoE related products such as the CAT5 to Coax cable Managed Ethernet Midspan receiver eBridge4PCRX and the transceiver with integral managed PoE/PoE+ switch eBridge4SK. VB6 provides two sets of output terminals to facilitate connection for up to two devices. It is powered by a 24VDC/24VAC Class 2 rated transformer/power supply.

Specifications

Input:

- 24VAC @ 1.5 amp or 24VDC @ 1.5 amp.

Output:

- Two (2) 56VDC outputs with up to 30W combined total power.
- Electronically filtered and regulated outputs.
- Built-in overload protection.

Features:

- Input and Output LEDs.
- Spring terminals.

Mechanical:

- Lightweight molded compact insulated housing.
- Dimensions (W x D x H approx.): 3.5" x 3.5" x 1" (88.89mm x 88.89mm x 25.4mm).
- Product weight (approx.): 0.25 lbs. (0.11 kg).
- Shipping weight (approx.): 0.3 lbs. (0.14 kg).

Agency Approvals



UL/CUL Listed for Information Technology Equipment (UL 60950-1).

CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.



European Conformity