# Concord Two-Way Voice LCD Keypad

Keypad for use with Concord Systems

## OVERVIEW

The Concord® Two-Way Voice LCD Keypad controls Concord 4 panels and provides integrated two-way voice operation with a central station operator. Messages indicating the current status of the system are displayed in a large and easy-to-see LCD window, and emergency keys are highlighted on the keypad for added safety and convenience.

The keypad can be used for installer/user programming of the Concord control panels and has the capability of displaying customized zone-naming text.

A built-in speaker emits sounds to indicate alarm, status, and when a button has been pressed. The swing-down door reveals the control keys and a label showing basic system operating commands. The door may be removed for quick access to buttons and applications where a black keypad is desired.

## STANDARD FEATURES

- Easy to install
- Large easy-to-read display
- Multi-color status indicator
- Integrated two-way voice
- Programmable stand-alone panic keys
- Stand-alone arming keys
- White door/black front can blend with any décor

## Specifications

| | |
|---|---|
| Compatibility | Concord 4 and later |
| **Electrical** | |
| Voltage | 12VDC nominal |
| Current | 60mA typical, 110mA in alarm |
| **Environmental** | |
| Operating Temperature | 32ºF~120ºF (0ºC~49ºC) |
| Humidity | 85% max. (non-condensing) |
| **Physical** | |
| Dimensions (LxWxD) | 5.3 x 6.0 x 0.9 in. (135 x 153 x 2mm) |
| **Regulatory** | |
| | UL (985, 1023, 1610) |
| | cUL (S545, 1023, S304) |

## Ordering Information

| | |
|---|---|
| **600-1070** | Concord Two-Way Voice LCD Keypad |

interlogix
United Technologies

interlogix.com

Specifications subject to change without notice.

© 2015 United Technologies Corporation.
All rights reserved.
All trademarks are the property of their respective owners.
Interlogix is part of UTC Building & Industrial Systems,
a unit of United Technologies Corporation.

505-3932 2015/05 (81894)