

IPP-AL400-ULPS Power Supplies (4.0 A)

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Filtered and electronically regulated outputs
- ▶ Short circuit and thermal overload protection
- ▶ Built-in charger
- ▶ Automatically switches to standby battery when AC fails
- ▶ Three supervision outputs

The IPP-AL400-ULPS is a switching power supply and charger. It converts 115 VAC, 50 Hz to 60 Hz input into single 12 VDC or 24 VDC Class 2 Rated power-limited output.

Functions

Supervision Monitoring

The IPP-AL400-ULPS Power Supply monitors three independent outputs for the following failure conditions:

- AC failure
- Low battery
- Battery presence

Certifications and approvals

Either Bosch Security Systems, Inc. or Altronix® holds the following Listings and Approvals:

Region	Certification
USA	UL Bosch Security Systems, Inc. - AMCX.S1871, Central Station Alarm Units; AOTX.S1871, Local Alarm Units; APAW.S1871, Police Station-connected Alarm Units; APOU.S1871, Proprietary Alarm Units; NBSX.S1871, Household Burglar Alarm System Units; UOXX.S5579, Control Unit Accessories,

Region	Certification
	System; UTOU.S1871, Control Units and Accessories, Household System Type
	UL Altronix Corporation - ALVY: Access Control System Units (ANSI/UL294), APHV: Power Supplies for Use with Burglar-Alarm Systems (ANSI/UL603), NBRZ: Hospital Signaling and Nurse Call Equipment (ANSI/UL1069), and UTRZ: Power Supplies for Fire-Protective Signaling Systems (UL1481)
	CSFM 7300-1615: 226 7300 -- FIRE ALARM CONTROL UNIT ACCESSORIES/MISC. DEVICES

Installation/configuration notes

Compatibility Information

The IPP-AL400-ULPS is compatible with any device requiring 12 VDC or 24 VDC. The ULPS enclosure and the following modules have been listed for use together:

- IPP-AL400-ULPS Power Supply
- IPP-PD4-ULCB Power Distribution Module
- C900V2 Dialer Capture Module
- D9210C Access Control Interface Module
- B426 Ethernet Communication Module

Mounting Considerations

The IPP-AL400-ULPS enclosure has two three-hole mounting patterns. The mounting pattern will support any one of the following combinations:

- Two B426 Ethernet Communication Modules
- Two D9210C Access Control Interface Modules
- One B426 and one D9210C

The enclosure also supports up to two Conettix IP C900V2 Dialer Capture Modules and one IPP-PD4-ULCB Power Distribution Module.

Technical specifications

Electrical

Power Input

Voltage:	115 VAC, 50 Hz to 60 Hz
Current:	1.45 A
Input Fuse:	3.5 A, 250 V Short circuit and thermal overload protection

Power Output

Voltage:	12 VDC or 24 VDC, selectable
Current:	12 VDC at 4 A 24 VDC at 3 A
Class:	Class 2 Rated power limited

Battery Power

Maximum Charge Current Output:	7 A
Type:	Sealed lead-acid or gel-type batteries

Mechanical

Enclosure Dimensions:	51.8 cm x 41.3 cm x 10.2 cm (20.375 in. x 16.25 in. x 4 in.)
Material:	Red steel, 1.2 mm thick
Supervision Outputs:	Three <ul style="list-style-type: none"> • AC Failure (Form C contacts) • Low Battery (Form C Contacts) • Battery Presence (Form C Contact)

Trademarks

Altronix® is a registered trademark of Altronix Corp.

Ordering information

IPP-AL400-ULPS Power Supply

Includes one power supply and one enclosure.

Order number **IPP-AL400-ULPS**

IPP-AL400-ULPS Power Supply Kit 1

Includes one power supply, one enclosure, and one IPP-PD4-ULCB Power Distribution Module.

Order number **IPP-AL400-ULK1**

IPP-AL400-ULPS Power Supply Kit 2

Includes one power supply, one enclosure, one IPP-PD4-ULCB Power Distribution Module, and one B426 Ethernet Communication Module.

Order number **IPP-AL400-ULK2**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com