

# E90 Low-profile Speakers

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ 24 VDC, filtered or unfiltered
- ▶ 25 VRMS or 70 VRMS operation at a choice of five taps from 0.125 W to 2 W
- ▶ Cost-effective two-wire design
- ▶ Easy wiring via screw terminals
- ▶ Supervised inputs

The E90 Speakers provide high audio output with clear audibility, and are designed to meet the critical needs of the life safety industry for effective emergency voice communications and tone signaling. The high-efficiency speakers are designed for maximum output at a minimum wattage across a frequency range of 400 Hz to 4 kHz.

A speaker mounting plate with a built-in level adjustment allows for a faster and easier installation. The two-screw grill cover creates an attractive appearance.

## Certifications and approvals

Cooper Wheelock, Inc. holds these Listings and Approvals:

Region	Certification	
USA	UL	UEAY: Speakers (UL464), UUKC: Signaling Appliances and Equipment for the Hearing Impaired (UL1971), UUMW: Speakers and Amplifiers for Fire Protective Signaling Systems (UL1480, UL1711, and UL2043)
	CSFM	see our website

## Installation/configuration notes

### Compatible Products

The following products are compatible with the E90 Speakers:

Category	Product ID	Product Description
Control Panels	D7022 <sup>1</sup>	Conventional FACP
	D7024	Conventional or Addressable <sup>2</sup> FACP
	FPD-D7024	Conventional or Addressable <sup>2</sup> FACP
	D8024	Analog FACP
	D9124	Addressable FACP
	D10024A	Analog FACP

These speakers are compatible with Wheelock SAFEPATH4 Facility Communication Systems and Bosch Voice Evacuation Systems.

<sup>1</sup> When used, the D7022 must be set for 24 VDC operation.

<sup>2</sup> When used with a D7039 Multiplex Expansion Module, the D7024 and FPD-7024 become addressable fire alarm control panels (FACPs).

### Mounting

The low profile design of these notification appliances creates more wiring space in standard electrical back boxes. The speaker mounting plate incorporates a built-in level adjustment feature allowing for a faster and easier installation. These speakers mount on the indicated back boxes for the indicated applications:

	Conduit Applications	Surface Mounted	Flush Mounted
Four-inch square*			•
SBB Back Box	•	•	

\* Requires an SER extension ring.

### Wiring

The input terminals accept wires with diameters between 18 AWG and 12 AWG (ISO 0.75 mm<sup>2</sup> and 4 mm<sup>2</sup>).

### Parts included

Quant.	Component
1	Speaker
1	Mounting Plate
1	Hardware pack
1	Literature pack

### Technical specifications

#### Electrical

##### Power Requirements

Voltage (input):	24 VDC nominal; 16 VDC or FWR to 33 VDC or FWR
------------------	---

#### Environmental

Relative Humidity:	Up to 85%, non-condensing
Temperature (Operating):	0° to +49°C (+32°F to +120°F)

#### Mechanical

Dimensions (diameter x D):	7.25 in. x 2.9 in. (18.4 cm x 7.5 cm)
Material:	Molded plastic

#### Speaker Volume at 10 ft (3 m)

0.125 (1/8) W:	77.5 dBA
0.25 (1/4) W:	80.4 dBA
0.5 (1/2) W:	83.2 dBA
1 W:	85.7 dBA
2 W:	87.8 dBA

### Ordering information

#### E90-N Low-Profile Speaker (nickel)

Nickel finish, 24 VDC device with high audio output with clear audibility, dual voltage capability (25 VRMS or 70 VRMS), and field-selectable taps from 1/8 W to 2 W

Order number **E90-N**

#### E90-W Low-Profile Speaker (white)

White, 24 VDC device with high audio output with clear audibility, dual voltage capability (25 VRMS or 70 VRMS), and field-selectable taps from 1/8 W to 2 W

Order number **E90-W**

#### Accessories

##### SBB-R Surface-mount Back Box (red)

14 cm (5.5 in.) x 14.2 cm (5.6 in.) x 9.1 cm (3.6 in.)

Order number **SBB-R**

##### SBB-W Surface-mount Back Box (white)

14 cm (5.5 in.) x 14.2 cm (5.6 in.) x 9.1 cm (3.6 in.)

Order number **SBB-W**

##### SER-R Square Semi-flush Extension Ring (red)

12.7 cm (5 in.) square by 4 cm (1.5625 in.) deep

Order number **SER-R**

##### SER-W Square Semi-flush Extension Ring (white)

12.7 cm (5 in.) square by 4 cm (1.5625 in.) deep

Order number **SER-W**

##### SSB-4 Ceiling Support Bridge

60.3 cm (23.75 in.) long by 16.5 cm (6.5 in.) wide

Order number **SSB-4**

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com