

ET70WP Weatherproof Speaker Strobes

www.boschsecurity.com



BOSCH
Invented for life



The ET70WP Weatherproof Speaker Strobes provide high audio output with clear audibility, and are designed to meet the critical needs of the life safety industry for effective emergency voice communications, tone signaling, and visible signaling. The strobe is rated for 75 cd light intensity on axis at -31°F (-35°C).

A speaker mounting plate with a built-in level adjustment allows for a faster and easier installation. The two-screw grill cover creates an attractive appearance.

The high-efficiency speaker is designed for maximum output at a minimum wattage across a frequency range of 400 Hz to 4 kHz. The speaker has seven power taps from 0.125 W to 8 W.

When used with the SM (single) or DSM (dual) Synchronization Modules, the strobe produces a synchronized flash for compliance with ADA guidelines concerning photosensitive epilepsy. All strobe input is compatible with standard reverse polarity type supervision of circuit wiring by a fire alarm control panel (FACP).

- ▶ Wall-mount and ceiling-mount models
- ▶ Weatherproof from -31°F to +150°F (-35°C to +66°C)
- ▶ 25 VRMS or 70 VRMS operation at a choice of seven taps from 0.125 W to 8 W
- ▶ Cost-effective two-wire design with easy-to-wire screw terminals
- ▶ Supervised inputs



Notice

These products are not suitable for hearing-impaired applications.

Certifications and approvals

Cooper Wheelock, Inc. holds these Listings and Approvals:

Region	Certification
USA	UL UEAY: Speakers (UL464), UUKC: Signaling Appliances and Equipment for the Hearing Impaired (UL1971), UUMW: Speakers and Amplifiers for Fire Protective Signaling Systems (UL1480, UL1711, and UL2043)
	CSFM see our website

Installation/configuration notes

Compatible Products

The following products are compatible with the ET70WP Weatherproof Speaker Strobes:

Category	Product ID	Product Description
Control Panels	D7022 ¹	Conventional FACP
	D7024 ²	Addressable FACP
	D7024	Conventional FACP
	D8024 ¹	Analog FACP
	D9124 ¹	Addressable FACP
	D10024A ¹	Analog FACP
	FPA-1000	Analog Addressable FACPs
	FPD-7024 ²	Addressable FACP
	FPD-7024	Conventional FACP
Modules	SM-12/24-R	Synchronization module (red)
	DSM-12/24-R	Dual synchronization module (red)

These speakers are compatible with Wheelock SAFEPATH4 Facility Communication Systems and Bosch Voice Evacuation Systems.

¹ For synchronization, use the SM or DSM module with these control panels. Set the synchronization module for 24 V operation. When used, set the D7022 for 24 VDC operation.

² When used with a D7039 Multiplex Expansion Module, the D7024 and FPD-7024 become addressable fire alarm control panels (FACPs).

Mounting

The low profile design of these notification appliances creates more wiring space in standard electrical back boxes. The speaker mounting plate incorporates a built-in level adjustment feature allowing for a faster and easier installation.

These speaker strobes wall mount on the indicated back boxes for the indicated applications:

	Conduit Applications	Surface Mounted	Flush Mounted
IOB Back Box	•	•	

Outdoor or Severe Environment Applications

For an outdoor or a severe environment (NEMA 3R) application, mount the speaker strobe with an IOB Indoor or Outdoor Back Box on a flat wall or ceiling so the entire rear surface of the back box is covered. The drain holes in the back box must point toward the ground. The knockouts on the rear surface of the back box must remain intact.

The knockout hole on top of the back box is sized for a half-inch conduit and matching connector. Use a watertight conduit fitting.

Wiring



Notice

Do not use the strobe unit in coded or pulsed signaling circuits.

The input terminals accept wires with diameters between 18 AWG and 12 AWG (ISO 0.75 mm² and 4 mm²).

Parts included

Quant.	Component
1	Weatherproof Speaker Strobe
1	Mounting plate
1	Hardware pack
1	Literature pack

Technical specifications

Electrical

Strobe Current at 75 cd (RMS maximum)

VDC:	138 mA
VFWR:	222 mA

Voltage (input)

Nominal:	24 VDC
Range:	16 VDC or FWR to 33 VDC or FWR

Environmental

Relative Humidity:	Up to 95%, non-condensing
Temperature (Operating):	-31°F to +150°F (-35°C to +66°C)

Mechanical

Candela Rating (on axis):	75 cd at -31°F (-35°C) 180 cd at +77°F (+25°C)
Dimensions (H x W x D):	5.1 in. x 5.1 in. x 5.2 in. (13.0 cm x 13.0 cm x 13.3 cm)
Material:	Molded plastic enclosure incorporating a Xenon flashtube and Lexan lens.

Speaker Volume at 10 ft (3 m)

0.125 (1/8) W:	77 dBA
0.25 (1/4) W:	80 dBA
0.5 (1/2) W:	83 dBA
1 W:	86 dBA
2 W:	88 dBA
4 W:	91 dBA
8 W:	93 dBA

Trademarks

All hardware and software product names used in this document are likely to be registered trademarks and must be treated accordingly.

Ordering information

ET70WP-2475W-FR Wall-mount Weatherproof Speaker Strobe (red)

Red, wall-mount, 24 VDC weatherproof device providing high audio output with clear audibility, dual voltage capability (25 VRMS or 70 VRMS), field-selectable taps from 1/8 W to 8 W, and strobe rated for light intensity on axis of 75 cd at -31°F (-35°C) and 180 cd at +77°F (+25°C)
Order number **ET70WP-2475W-FR**

ET70WP-2475C-FR Ceiling-mount Weatherproof Speaker Strobe (red)

Red, ceiling-mount, 24 VDC weatherproof device providing high audio output with clear audibility, dual voltage capability (25 VRMS or 70 VRMS), field-selectable taps from 1/8 W to 8 W, and strobe rated for light intensity on axis of 75 cd at -31°F (-35°C) and 180 cd at +77°F (+25°C)
Order number **ET70WP-2475C-FR**

ET70WP-2475C-FW Ceiling-mount Weatherproof Speaker Strobe (white)

White, ceiling-mount, 24 VDC weatherproof device providing high audio output with clear audibility, dual voltage capability (25 VRMS or 70 VRMS), field-selectable taps from 1/8 W to 8 W, and strobe rated for light intensity on axis of 75 cd at -31°F (-35°C) and 180 cd at +77°F (+25°C)
Order number **ET70WP-2475C-FW**

Accessories

IOB-R Indoor or Outdoor Back Box (red)

13.3 cm (5.25 in.) square, 6.7 cm (2.625 in.) deep
Order number **IOB-R**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com