

# MIZ Piezoelectric Mini-horns

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Operates on 24 VDC, filtered or unfiltered
- ▶ Field-selectable settings for temporal (Code 3) or continuous horn
- ▶ High sound output (90 dBA at 10 ft [3 m])
- ▶ Low current draw on two-wire loop
- ▶ Low temperature compensation

These Wheelock mini-horns are dual-tone alarm devices listed for indoor use under UL464 for Audible Appliances. They combine a low current draw for a high sound output and offer field-selectable tone settings for temporal (Code 3) or continuous horn tones. They use either filtered DC or unfiltered full wave rectified (FWR) input voltage. All inputs are polarized for standard reverse polarity supervision. They can be synchronized when used with the SM (single) and DSM (dual) Synchronization Modules or a compatible control panel. If not synchronized, the temporal sound patterns could overlap and not be distinctive.

Available in red for high visibility or off-white to blend in with room decor, these notification appliances offer the durability of high impact thermoplastic construction, easy installation through two-wire circuitry and single-gang box compatibility. They are ideal audible notification appliances for signaling alarms in individual rooms in apartments, hotels, motels, and offices.

## Certifications and approvals

Cooper Wheelock, Inc. holds these Listings and Approvals:

Region	Certification	
USA	UL	UCST: Audible Signal Appliances, General Signal (UL464), ULSZ: Audible Signal Appliances (UL464)
	FM	MIZ Family
	CSFM	see our website
Canada	ULC	ULSZC: Audible Signal Appliances, Fire Alarm, Including Accessories (CAN/ULC-S525 and ULC-S527)

## Installation/configuration notes

### Compatible Products

The following products are compatible with the MIZ Mini-horns:

Category	Product ID	Product Description
Control Panels	FPA-1000	Analog Addressable FACPs
	FPD-7024 <sup>1</sup>	Addressable FACP
	FPD-7024	Conventional FACP
	D7024 <sup>1</sup>	Addressable FACP
	D7024	Conventional FACP
	D8024 <sup>2</sup>	Analog FACP
	D9124 <sup>2</sup>	Addressable FACP

	D10024A <sup>2</sup>	Analog FACP
Modules	SM-12/24-R	Single synchronization module (red)
	DSM-12/24-R	Dual synchronization module (red)

<sup>1</sup> When used with a D7039 Multiplex Expansion Module, the FPD-7024 or D7024 become addressable fire alarm control panels (FACPs).

<sup>2</sup> For synchronization, use the SM or DSM Synchronization Modules with these control panels.

### Mounting Considerations

Mount these mini-horns on the indicated back boxes for the indicated applications:

	Conduit Applications	Surface Mounted	Flush Mounted
Single-gang, wiremold		•	
Single-gang, deep	•		•

### Wiring

The input terminals accept wires with diameters between 18 AWG and 12 AWG (ISO 0.75 mm<sup>2</sup> and 4 mm<sup>2</sup>).

### Parts included

Quant.	Component
1	MIZ-24S-R or MIZ-24S-W Mini-horn
1	Hardware pack
1	Literature pack

### Technical specifications

#### Electrical

Maximum Horn Current (RMS, operating):	VDC: 26 mA FWR: 43 mA
Voltage (nominal input):	24 VDC or FWR
Voltage (operating range):	16 V to 33 VDC or FWR

#### Environmental

Relative Humidity:	Up to 93%, non-condensing
Temperature (Operating):	+32°F to +120°F (0°C to +49°C)

#### Mechanical

Dimensions (H x W x D):	4.5 in. x 2.75 in. x 1.375 in. (11.4 cm x 7.0 cm x 3.5 cm)
Material:	High-impact thermoplastic

### Sound Output (UL Reverberant Room) at 10 ft (3 m)

Continuous:	16 VDC: 79 dBA 24 VDC: 83 dBA 33 VDC: 85 dBA
Temporal (Code 3):	16 VDC: 75 dBA 24 VDC: 78 dBA 33 VDC: 81 dBA



#### Notice

The sound output for the temporal Code 3 is lower than in Continuous mode because the time that the horn is off is averaged into the sound output rating. While the horn is producing a tone in temporal Code 3 modes, its sound pressure is the same as the Continuous mode.

### Ordering information

#### MIZ-24S-R 24 V Mini-horn (red)

Red, 24 VDC dual-tone alarm device with low current draw, high sound output, and field-selectable settings for temporal (Code 3) or continuous horn tones  
Order number **MIZ-24S-R**

#### MIZ-24S-W 24 V Mini-horn (white)

White, 24 VDC dual-tone alarm device with low current draw, high sound output, and field-selectable settings for temporal (Code 3) or continuous horn tones  
Order number **MIZ-24S-W**

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com