

Buffer-Expander Volume Control Model BUFEX



Description The BUFEX is a continuously variable speaker attenuator that can remotely control the volume of a network of speakers. The BUFEX also provides output buffering for up to 150 self-amplified speaker inputs and allows speaker system expansion of existing 100V, 70V, or 25V central amplifier systems. The BUFEX includes a bypass function that can override the volume control knob setting when activated by a contact closure or open collector output. This allows emergency announcements to be heard through all speakers in a system even if the volume control knob setting is set low or off. A PCB-mounted bypass trim control adjusts the volume when in bypass mode with a maximum of 12 dB of attenuation. The BUFEX fits into a single gang electrical box.

- Features**
- Continuously variable attenuator
 - Drive up to 150 self-amplified speaker inputs
 - 100V, 70V, 25V, and page port level selectable input
 - Bypass trim control for emergency paging (12 dB of preset control over level of bypass announcements)
 - Mounts in a single gang electrical box
 - Rugged and attractive stainless steel plate with engraved lettering
 - Easy and secure terminal strip connections
 - Two-Year Warranty

Technical Specifications	Supply Voltage: 24V DC	Bypass Trip Current: 0.8 mA
	Current Consumption: 1 CU (50 mA)	Speaker Drive Capacity: 150 Self-Amplified Speakers
	Output Impedance: 8 ohms	Input Compatibility: 100V, 70V, and 25V
	Volume Control Range: 0 to -50 dB	Dimensions: 2-7/8" W x 4-5/8" H x 2-1/2" D
	Bypass Voltage: 10V	Product Weight: 3 oz.

Architect & Engineer Specifications

The Level Controller shall be a continuously variable speaker attenuator that can remotely control the volume of a network of speakers, Bogen Model BUFEX. It shall provide output buffering for up to 150 self-amplified speaker inputs and allow speaker system expansion of existing 100V, 70V, or 25V central amplifier systems.

The BUFEX shall include a bypass function for overriding the volume control knob setting when activated by a contact closure or open collector output. A PCB-mounted bypass trim control shall adjust the volume when in bypass mode with a maximum of 12 dB of attenuation.

The BUFEX power consumption shall be 1 CU (50 mA) @ 24V DC.

The Tip (T) and Ring (R) connections shall be audio outputs with an output impedance of 8 ohms.

The BUFEX shall have a rugged and attractive stainless steel plate with engraved lettering.

The BUFEX shall measure 2-7/8" W x 4-5/8" H x 2-1/2" D and fit into a single gang electrical box. The BUFEX shall weigh 3 ounces.



Signal Level Control Model SLC



Description The SLC is a continuously variable volume control that can remotely control the volume of up to 150 self-amplified speakers. The SLC fits into a single gang electrical box.

- Features**
- Remotely control the volume of up to 150 self-amplified speakers
 - Rugged and attractive stainless steel plate with engraved lettering
 - Mounts in a single gang electrical box
 - Easy and secure terminal strip connections
 - Passive (requires no DC power)
-

Technical Specifications Max. Speaker Capacity: 150
Dimensions: 2-7/8" W x 4-5/8" H x 2" D
Product Weight: 2 oz.

Architect & Engineer Specifications The Level Controller shall be a continuously variable passive volume control that can remotely control the volume of up to 150 self-amplified speakers, Bogen Model SLC. The SLC output terminals shall be able to control up to 150 speaker inputs. Output wiring shall be made via two separate two-position screw terminal blocks for input and output signals.

The SLC shall have a rugged and attractive stainless steel plate with engraved lettering.

The SLC shall measure 2-7/8" W x 4-5/8" H x 2" D and fit into a single gang electrical box. The SLC shall weigh 2 ounces.

BOGEN[®]
COMMUNICATIONS, INC.

50 Spring Street, Ramsey, NJ 07446, U.S.A.
Tel.: 201-934-8500 • Fax: 201-934-9832
www.bogen.com