



- 1/3" color SONY Super HAD CCD image sensor
- Motorized camera for a greater angle of view (up and down motion)
- Weatherproof camera
- IR LED for night illumination
- CDS sensor for automatic IR LED activation
- Built-in microphone

# SPECIFICATION

### Image sensor

1/3" color SONY Super HAD (270K Pixels)

### Effective pixels

NTSC (525TVL): 512(H) x 492(V)

PAL (625TVL): 512(H) x 582(V)

### Scanning system

2:1 interlaced

### H. resolution

NTSC / PAL - 380TVL

### Scanning frequency

Horizontal: 15,734Hz, Vertical: 59.94Hz

### Video output level

1.0Vp-p (75Ω composite)

### S/N ratio

More than 50dB (AGC off)

### Gamma

r=0.45

### White balance

2,100°K ~ 5600°K - Auto

### Min. illumination

1.0 Lux (IR LED off) / 0 Lux (IR LED on)

### Electronic shutter

1/60 ~ 1/100,000sec; 1/50 ~ 1/100,000sec

### IR LED

Visible 5mm diameter (850nm, 30° x 8ea)

### Visibility range

Real 5 meter (approx. 16 Feet)

### CDS sensor

IR LED on/off at 5.0 Lux

### Motor control angle

Up & down (center ±45°)

### Audio

1 way (to monitor)

### Operating temperature

-30°C ~ +80°C (-22°F ~ +176°F)

### Humidity

10% ~ 95% RH

### Lens

STD lens: fix 2.4mm lensF: 1.8

### Power source

DC12V 120mA (max. 200mA)

### Dimensions (Inch)

3.66(W) x 2.76(H) x 2.79(D)

### Weight (approx.)

380g (0.83lbs)

### Cable

Round din 6 pin locking type

# Rear View Motorized Camera with IR LED

## DIMENSIONS (Unit: mm)

WDRV-7063C

