

CS8 Ceiling speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 8" paper speaker cone, 3 Watts RMS max.
- Built in ETS LT870 70v line transformer.
- Easy cable termination.
- Mounting hardware included.



CS4 Ceiling / flush mount speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 4" Mylar speaker cone, 3 Watts RMS max.
- Built in ETS LT870 70v line transformer.
- Easy cable termination.
- Mounting hardware included.

WS4 wall / surface mount speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 4" Mylar speaker cone, 3 Watts RMS max.
- Built in ETS LT870 70v line transformer.
- Easy cable termination.
- Mounting hardware included.



OS6 Outdoor speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 6" diagonal horn speaker, 3 Watts RMS max.
- Tough, cast aluminum housing.
- Built in tamper switch.
- Built in ETS LT870 70v line transformer.
- Easy cable termination.

HS5 Horn speaker For use with remote monitoring two-way audio surveillance systems or public address systems.

- 5" horn speaker, 3 Watts RMS max.
- Easy cable termination.
- Built in ETS LT870 70v line transformer
- Easy cable termination.
- Not recommended for outdoor use.



STW1 Two Way Microphone / speaker Omni-directional pre-amplified microphone and speaker for use in two way surveillance systems.

- Optional call switch (not shown) for paging listener.
- Stainless steel cover. Fits double gang boxes.
- Low noise MOSFET pre-amplifier.
- Line level unbalanced output. Adjustable gain.
- Limiter and treble boost circuits selectable on/off.
- Built in 2.25" speaker 0.5W and ETS LT870 70v line transformer.
- Power: 12VDC @ 10mA. On-board voltage regulator.
- Optional surface mount adapter.