



Electronic Technical Services Inc.
211 Conchas SE
Albuquerque, NM 87123
PH 505-888-3923 FAX 505-888-3926
Website: www.etsnm.com

Sound Surveillance™

SM1-SDU Covert smoke detector style, unidirectional microphone

Description

High performance, Unidirectional pre-amplified microphone for use where side noise must be reduced. Covert housing designed to appear exactly like a modern smoke detector. Simply mount the SM1-SDU in the direction of interest. Built in limiter circuit automatically lowers the output level during loud sound intervals. Selectable lo-cut and hi-cut filters significantly reduce background noise. Ivory ABS enclosure Mounts on any flat surface.

Connects directly to our switcher / mixer / amplifiers or use one of our many interface products to make fast and clean connections to DVRs or remote monitoring equipment.

Includes:

- SM1-SDU Microphone
- Warning label.
- Installation instructions.

Available with SM1-P pre-amplifier SM1-SDUP

Wiring requirements:

2 conductor shielded (with drain wire) 22 gauge stranded. Max cable length 1500'.

Caution

It is the responsibility of the installation company and end user to install this audio surveillance equipment in compliance with state and federal privacy laws. If you are unfamiliar with these laws, consult a qualified attorney.

Warranty 1 year parts and labor,

Made in USA



SM1-SDU Specifications

- Unidirectional 25' pickup pattern with reduced (-6db) sensitivity on all sides.
- Low noise MOSFET pre-amplifiers.
- 500Hz-13Khz Frequency response.
- Jumper selectable hi-cut/lo-cut filters limit frequency response to up to 900 to 6Khz significantly reducing background noise.
- Jumper selectable volume range: "Line level" (0db) or "Microphone level" (-30db)
- Adjustable gain in both volume ranges.
- Peak Limiter: .5sec response time
- 100 Ohm unbalanced output.
- 3 position Euro-style connector makes cable termination fast and clean.
- Power: 12 to 24VDC @ 10mA.
- On-board voltage regulator and RFI filtering.
- Industrial temperature range: -40C to 105C
- Ivory ABS enclosure Mounts on any flat surface.
- Dimensions: Dia. 4.00 x H1.80
- Weight: 0.09lbs