R S DIGITAL VIDEO SYSTEMS

The IRIS Digital Video Systems Series-960HD DVRs offer extreme versatility and flexibility for your surveillance installations. All systems accept a combination of analog, I.P., and HD-TVI (1080P) inputs, a wide selection of hard disk drive sizes, single channel audio recording, with 8-channel or 16-channel base configurations.

series OHD OVIS

In addition, the Series-960HD DVRs offer streaming to a web browser and a range of mobile devices.

For more complex management requirements, Central Management Software supports the remote viewing of up to 64 cameras, and configuration of multiple sites from one or more control centers.



Features:

- 8 or 16 channel video recording
- 4 or 8 channels of I.P. video
- H.264 video compression
- 1080P, 720P, WD1 & D1 recording
- PTZ Control Capable
- Mobile device support
- Supports up to 2 internal SATA HDD
- Scheduled recording
- Motion and alarm triggered recording

- Single channel gudio recording
- Per channel configuration
- Alarm recording
- On-screen motion-detection indicator
- GUI
- USB mouse
- HDMI & VGA monitor outputs
- Browser-based software
- IR remote control



IRIS products are endorsed by leading associations throughout the United States!



Specifications and Ordering Information

Item ▼	Туре ▶	8 Channel	16 Channel
Part Number	1 TB	6908-1T	6916-1T
	2 TB	6908-2T	6916-2T
	4 TB	6908-4T	6916-4T
	6 TB	6908-6T	6916-6T
Video Input		8 x BNC	16 x BNC
IP Video		4	8
Audio Input		1 x RCA in / 1 x RCA out	
Display Output		1 x VGA, 1 x HDMI	
Display Resolution		1920 x 1080	
Recording 720P/WD1/D1		240fps	480fps
Recording 1080P		120fps	240fps
Playback		8 channels simultaneously	
Compression Format		H.264	
Recording Formats		1080P (1920 x 1080), 720P (1280 x 720) WD1, D1	
Hard Disk Support		Up to 6TB, HDD x 2	
Recording Controls		Manual, Scheduled, Motion Triggered	
Network Interface		10/100Mbps, RJ45	
Network Protocols		DHCP/Static, PPoE, DDNS	
Internet Bandwidth		Configurable	
Network Ports		Administrator definable	
USB Ports		2	
Remote Access	, , , , , , , , , , , , , , , , , , , ,		
Mobile Device Support		Android, iPhone, iPad	
PTZ Control		RS485	
User Controls		Front Panel Buttons, Mouse, IR Remote	
Operating Temperature		-10°C~+50°C (14°F~122°F)	
Power Supply		DC12V < 4.0A (Main PSU Supplied)	
Dimensions (WxDxH)		430mm x 300mm x 55mm (16.92" x 11.81" x 2.16")	

Notes: Performance may vary based on actual set-up programming. Series-960HD DVRs do not interface with IRIS Inquiry.

Visit our website for information on our full line of digital video surveillance products.

www.iris-dvs.com



Three-year depot warranty. Products are RoHS compliant.