



**ULT-C2BXIRA550** Megapixel/1080p TVI Outdoor Bullet, 5-50mm Auto-Focus Motorized Lens, WDR, 300' EXIR Range, Dual Voltage

2 Megapixel

5-50mm  
Motorized Zoom

True  
Day/Night

True WDR

EXIR  
300' IR Range

UTC  
Up The Cable Control

IP66  
Weather Resistant


CVBS Output

Dual Voltage  
DC12V | AC24V

Features

- 2 Megapixel (1920 x 1080) Resolution
- Motorized Auto-Focus 5-50mm Lens
- True Day/Night
- True WDR 120dB
- 300' IR Range with EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Analog Video Output
- Dual Voltage

Mounting Options

 IUM-BRJB1:  
Large Bullet Junction Box #1

 IUM-BRCM1\*  
Corner Mount #1

 IUM-BRPM1\*  
Pole Mount #1

Ordering Information

**ULT-C2BXIRA550:** 2 Megapixel Motorized Auto-Focus Bullet, 5-50mm

Model Number	ULT-C2BXIRA550
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	1/25 s to 1/50,000s
Lens (Angle of View)	5-50mm (59.8° ~ 6.2°)
Auto Iris	Yes
Lens Mount	φ14
Day & Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	True WDR 120 dB
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 8 zones
Motion Defection	On / Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-4 °F ~ 140 °F (-20 °C ~ 60 °C)
Humidity	Humidity 90% or less (non-condensing)
Power Supply	12 VDC; 24 VAC
Power Consumption	12V DC: Max. 11W ; 24V AC: Max. 11W
Housing	IP66
IR Range	Up to 300 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron)
Dimensions	12.3 x 3.9 x 4.2 in (312.4 x 99 x 106.68mm)
Weight	3.75 lbs (1700g)

\*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

**2 MEGAPIXEL | 1080p**