



ULT-C2TIRM2812 2 Megapixel/1080p TVI Outdoor Turret, 2.8-12mm Motorized Lens, 150' IR Range, Dual Voltage

2 Megapixel	2.8-12mm Motorized Zoom	True Day/Night
IR 150' Range	UTC Up The Cable Control	IP66 Weather Resistant
Operates to -40° F	DC12V	

Features

- 2 Megapixel (1920 x 1080) Resolution
- Motorized 2.8-12mm Lens
- True Day/Night
- 150' IR Range
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- 12VDC Only Operation

Mounting Options



Turret Junction Box #1





IUM-BRPM1* Pole Mount #1

IUM-BRCM1* Corner Mount #1

Ordering Information ULT-C2TIRM2812: 2 Megapixel Motorized Turret, 2.8-12mm

*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

Image Sensor $1 / 3^{\circ}$ Progressive Scan CMOSSignal SystemPAL / NTSCEffective Pixels1920(H)*1080(V)Min. Illumination0.01 Lux @ (F1.2, AGC ON).0 Lux with IR 0.014 Lux @ (F1.4, AGC ON).0 Lux with IR 0.014 Lux @ (F1.4, AGC ON).0 Lux with IRShutter Speed1/25 s to 1/50.000sLens (Angle of View)2.8-12mmAuto IrisYesDay & NightIR Cut Filter with Auto SwitchWide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Grame Rate1080p @ 30fpsHD Video Output1 Analog HD outputS / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor. Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Consumption12V DCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ffCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(-Coxitron)Dimensions ϕ 5.1 x 4 in (ϕ 129.5	Model Number	ULT-C2TIRM2812	
Effective Pixels1920(H)*1080(V)Min. Illumination0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IRShutter Speed1/25 s to 1/50,000sLens (Angle of View)2.8-12mmAuto IrisYesDay & NightIR Cut Filter with Auto SwitchWide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD outputS / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offCanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicEurotionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Consumption12V DCPower Consumption12V DCPower Consumption12V DC Imax.5WHousingIP66IR RangeUp to 120 ffCommunicationWo the coax(need UTC controller) Protocol: Pelco-C	Image Sensor	1 / 3" Progressive Scan CMOS	
Min. Illumination0.01 Lux @ (F1.2, AGC ON).0 Lux with IR 0.014 Lux @ (F1.4, AGC ON).0 Lux with IRShutter Speed1/25 s to 1/50.000sLens (Angle of View)2.8-12mmAuto IrisYesDay & NightIR Cut Filter with Auto SwitchWide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD outputS / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Miror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Consumption12V DCPower Consumption12V DCPower Consumption12V DCPower Consumption12V DC (max. 5WHousingIP66IR RangeUp to 120 ffDimensions ϕ 5.1 x 4 in (ϕ 129.54 x 101.6mm) <td>Signal System</td> <td colspan="2">PAL / NTSC</td>	Signal System	PAL / NTSC	
Niln. Illumination(F1.4, AGC ON), 0 Lux with IRShutter Speed1/25 s to 1/50,000sLens (Angle of View)2.8-12mmAuto IrisYesDay & NightIR Cut Filter with Auto SwitchWide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD output\$ / N RatioMore than 52dBSceneIndoor, Outdoor, Indoorl, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanisk, Russian, Portuguese, Dutch, Turkish, Henbrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ffCommunicationWo the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron)Dimensions ϕ 5.1 x 4 in (ϕ 129.54 x 101.6mm)	Effective Pixels	1920(H)*1080(V)	
Lens (Angle of View)2.8-12mmAuto IrisYesDay & NightIR Cut Filter with Auto SwitchWide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD output\$ / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Consumption12V DCPower Supply12 VDC	Min. Illumination		
Auto IrisYesDay & NightIR Cut Filter with Auto SwitchWide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD outputS / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionElcipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower	Shutter Speed	1/25 s to 1/50,000s	
InstrumInstructDay & NightIR Cut Filter with Auto SwitchWide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD outputS / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Consumption12V DCPower Consumption12V DCPower Consumption12V DCPower Consumption12V DCPower Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ffCommunicationUp the coax(need UIC controller) Protocol: Pelco-C(-Coaxitron)Dimensions ϕ 5.1 x 4 in (ϕ 129.54 x 101.6mm)	Lens (Angle of View)	2.8-12mm	
Wide Dynamic RangeDWDRSynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD output\$ / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron)Dimensions $\phi5.1 x 4 \ln (\phi 129.54 x 101.6mm)$	Auto Iris	Yes	
SynchronizationInternal synchronizationVideo Frame Rate1080p @ 30fpsHD Video Output1 Analog HD output\$ / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageErglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionÉclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C -60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftDimensionsφ5.1 x 4 in (φ 129.54 x 101.6mm)	Day & Night	IR Cut Filter with Auto Switch	
Video Frame Rate1080p @ 30fpsHD Video Output1 Analog HD output\$ / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionshutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftDimensionsq5.1 x 4 in (q 129.54 x 101.6mm)	Wide Dynamic Range	DWDR	
HD Video Output1 Analog HD output\$ / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionshutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftDimensionsq5.1 x 4 in (q 129.54 x 101.6mm)	Synchronization	Internal synchronization	
S / N RatioMore than 52dBSceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftDimensions\u03bbla 51 x 4 in (\u03bbla 129.54 x 101.6mm)	Video Frame Rate	1080p @ 30fps	
SceneIndoor, Outdoor, Indoor1, LOW-LIGHTCamera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Halian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftDimensions\u03cbi X 4 in (\u03cbi 129.54 x 101.6mm)	HD Video Output	1 Analog HD output	
Camera IDOn/off (15 characters, position programmable)AGCSupportD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(- Caaxitron)Dimensions φ 5.1 x 4 in (ψ 129.54 x 101.6mm)	S / N Ratio	More than 52dB	
AGC Support D/N Mode Color/BW/EXT White Balance ATW, AWC-SET, Indoor, Outdoor, Manual Privacy Mask On/Off, maximum 2 zones Motion Detection On / Off, maximum 4 zones BLC Support Anti-flicker On/off Language English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic Function Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM Working Temperature / Humidity -40 °C - 60 °C (-40 °F - 140 °F) Humidity Humidity 90% or less (non-condensing) Power Supply 12 VDC Power Supply 12 VDC Power Consumption 12V DC: Max. 5W Housing IP66 IR Range Up to 120 ft Communication Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)	Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT	
D/N ModeColor/BW/EXTD/N ModeColor/BW/EXTWhite BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron)Dimensions φ 5.1 x 4 in (ϕ 129.54 x 101.6mm)	Camera ID	On/off (15 characters, position programmable)	
White BalanceATW, AWC-SET, Indoor, Outdoor, ManualPrivacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron)Dimensions φ 5.1 x 4 in (ϕ 129.54 x 101.6mm)	AGC	Support	
Privacy MaskOn/Off, maximum 2 zonesMotion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron)Dimensionsφ5.1 x 4 in (φ 129.54 x 101.6mm)	D/N Mode	Color/BW/EXT	
Motion DetectionOn / Off, maximum 4 zonesBLCSupportAnti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron)Dimensionsφ5.1 x 4 in (φ 129.54 x 101.6mm)	White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual	
BLC Support Anti-flicker On/off Language English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic Function Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM Working Temperature / Humidity -40 °C - 60 °C (-40 °F - 140 °F) Humidity Humidity 90% or less (non-condensing) Power Supply 12 VDC Power Consumption 12V DC: Max. 5W Housing IP66 IR Range Up to 120 ft Communication Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)	Privacy Mask	On/Off, maximum 2 zones	
Anti-flickerOn/offLanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationØp 51 x 4 in (\u03c6 129.54 x 101.6mm)	Motion Detection	On / Off, maximum 4 zones	
LanguageEnglish, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron)Dimensions φ 5.1 x 4 in (ϕ 129.54 x 101.6mm)	BLC	Support	
LanguageFrench, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and ArabicFunctionEclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron)Dimensions $\varphi 5.1 \times 4 \ln (\varphi 129.54 \times 101.6mm)$	Anti-flicker	On/off	
Functionshutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOMWorking Temperature / Humidity-40 °C - 60 °C (-40 °F - 140 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron)Dimensionsφ5.1 x 4 in (φ 129.54 x 101.6mm)	Language	French, Italian, Spanish, Polish, Russian, Portuguese,	
HumidityLat C = 60 °C (-20 °F = 120 °F)HumidityHumidity 90% or less (non-condensing)Power Supply12 VDCPower Consumption12V DC: Max. 5WHousingIP66IR RangeUp to 120 ftCommunicationUp the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron)Dimensions $\phi 5.1 \times 4 $ in (ϕ 129.54 $\times 101.6$ mm)	Function	shutter, Mirror, Defog, Defect pixel correction, SMART	
Power Supply 12 VDC Power Consumption 12V DC: Max. 5W Housing IP66 IR Range Up to 120 ft Communication Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)		-40 °C – 60 °C (-40 °F – 140 °F)	
Power Consumption 12V DC: Max. 5W Housing IP66 IR Range Up to 120 ft Communication Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)	Humidity	Humidity 90% or less (non-condensing)	
Housing IP66 IR Range Up to 120 ft Communication Up the coax(need UTC controller) Protocol: Pelco-C(-Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)	Power Supply	12 VDC	
IR Range Up to 120 ft Communication Up the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)	Power Consumption	12V DC: Max. 5W	
Communication Up the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)	Housing	IP66	
Communication Coaxitron) Dimensions φ5.1 x 4 in (φ 129.54 x 101.6mm)	IR Range	Up to 120 ft	
	Communication		
Weight 0.9 lb (408g)	Dimensions	φ5.1 x 4 in (φ 129.54 x 101.6mm)	
	Weight	0.9 lb (408g)	