



ULT-C3DRXIRM2812 3 Megapixel TVI Outdoor Dome with 2.8-12mm Motorized lens, WDR, 120' EXIR Range, Dual Voltage



Features

- 3 Megapixel (2052 x 1536) Resolution
- Motorized 2.8-12mm Lens
- True Day/Night
- True WDR 120dB
- 120' IR Range with EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- IK10 Vandal Resistant
- Dual Voltage


Mounting Options







IUM-DRWM2:



IUM-DRPM2: Pendant Mount #2

| Ordering Information | |
|----------------------|--|
|----------------------|--|

ULT-C3DRXIRM2812: 3 Megapixel Motorized Dome, 2.8-12mm

To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

IUM-BRCM1*

IUM-BRPM1*

Pole Mount #1

Corner Mount #1

| Model Number | ULT-C3DRXIRM2812 |
|-----------------------------------|---|
| Image Sensor | 3MP CMOS |
| Signal System | PAL / NTSC |
| Effective Pixels | 2052(H)*1536(V) |
| Min. Illumination | 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR |
| Shutter Speed | 1/25 s to 1/50,000 s |
| Lens | 2.8-12mm @ F1.2 Motorized, Angle of view: 92° – 32° |
| Auto Iris | Yes |
| Day & Night | IR Cut Filter with Auto Switch |
| Wide Dynamic Range | 120dB True WDR |
| Synchronization | Internal synchronization |
| Video Frame Rate | 2052*1536@18fps |
| HD Video Output | 1 Analog HD output |
| S / N Ratio | More than 62dB |
| Scene | Indoor, Outdoor, Indoor1, Low-Light |
| Camera ID | On/off (15 characters, position programmable) |
| AGC | Support |
| D/N Mode | Color/BW/Smart |
| White Balance | ATW, MWB |
| Privacy Mask | Support |
| Motion Detection | On/Off, maximum 4 zones |
| BLC | Support |
| Anti-flicker | On/Off |
| Language | English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic |
| Function | Digital noise reduction, Digital zoom(62x) |
| Working Temperature / Humidity | -40 °F – 140 °F (-40 °C – 60 °C) Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC, 24VAC |
| Power Consumption | Max. 6.5W |
| Housing | IP66 Weather Resistant, IK10 Vandal Resistant |
| IR Range | Up to 120 ft |
| Communication | Up the coax(need UTC controller) Protocol: Pelco-C(- Coaxitron) |
| Dimensions | Ø5.72 x 4.89 in (145.2 x124.2mm) |
| Weight | 3.53 lbs |