

2 MEGAPIXEL | 1080p

PAR-C2TXIR

2 Megapixel/1080p TVI Turret, 3.6mm, 65' EXIR Range, TVI/AHD/Analog Output, 12VDC



1080p	TVI, AHD/CVBS	True Day/Night
D-WDR	EXIR 65' Range	UTC Up The Cable Control
IP66 Weather Resistant	DC12V	

Image Sensor	1/3" CMOS
Resolution	1920 x 1080
Image System	NTSC/PAL
Auto Iris	Fixed Iris
Min Illumination	0 Lux (IR On)
Lens	Fixed
Lens Mount	M12
IR Distance	65'
Environmental	IP66 Weather Resistant
Video Output	TVI & AHD / CVBS Selectable
Image Size	1080p (1920 x 1080)
Frame Rate	30 FPS (60Hz), 25 FPS (50Hz)
Angle Adjustment	3-Axis
Screen Display	2 Languages Supported (English & Chinese)
Function Control	OSD/UTC
Day & Night	Yes (ICR)
BLC & HLC	Yes
WDR	Digital WDR
Digital NR	Yes
Defect Correction	Live Defective Pixel Correction
S/N Ratio	>52dB (AGC Off)
Electronic Shutter	1/60s ~ 1/100000s (NTSC), 1/50s ~ 1/100000s (PAL)
AGC	Yes
White Balance	ATW, AWC-SET, Manual
Advanced Image	Adjustable Sharpness, Saturation, Brightness
Power Supply	DC12V (+ 10%)
Working Environment	-4° ~ 122° F (-20° ~ 50° C) 10%~90% Humidity
Dimensions	Ø 3.42 x 4.25" (Ø 87 x 108mm)

Features

- 2 Megapixel 1080p Resolution
- TVI & AHD/Analog Outputs
- Fixed Lens
- True Day/Night
- Digital Wide Dynamic Range
- EXIR Technology up to 65' IR Range
- UTC Function
- IP66 Weather Resistant
- 12VDC Operation

Ordering Information

PAR-C2TXIR36: 1080p Turret, 3.6mm

PARAMOUNT 