ELECTRONIC Two-way communication / Through A Partition



The SC-350 talk-through communicator is designed for applications where a fire shutter or window shade is present.



Made In U.S.A.

Two-way communication is accomplished through the use of speakers and microphones located on each side of the partition. The Master unit is equipped with a 15" gooseneck microphone, power on/off switch, power-on LED, and external volume controls. The Remote Unit is windowmounted and may incorporate a level 3 bullet-resistive insert.



Detention Facilities, Movie Theaters Hospitals, Banks, Subways, Ticket Booths and other security-sensitive areas

- Heavy Duty Aluminum Construction
- Dimensions of Master Unit: 2.8"x2.8"x8.0"
- Short Circuit Protection
- <1%^{*}Distortion
- Dynamic Noise Reduction Network
- Voice Activated Switch

- Duplex
 Communication
- Background Noise Level Monitoring
- Level Detection and Attenuation Control
- Low Current Drain
- Reverse Voltage and Voltage Protection

*Amplifier ratings

Features and specifications are subject to change without notice.



he SC-350 provides elctronic two-way, hands-free audio communications (duplex) between a partition. The SC-350 is equipped with a factory adjusted VOX switch to prevent ambient noise (below 85 decibels) from activating the unit. The SC-350 contains two voice channels, each incorporating a microphone amplifier, VOX switch, compressor, and a power amplifier. The sound amplifier does not exceed a 0.2% total harmonic distortion rating.

The SC-350 is fully operational between 0°C and 50°C.

Each order comes with an AC/DC power supply(120V AC stepped down to filtered 18V DC) and a 1-year warranty.

