



# SI004 and SI004/2 Illuminated Area of Rescue Assistance (or Refuge) Sign



SI004 (single sided)
SI004/2 (double sided)
Illuminated Area of Rescue Signs
Shown with different lamp positioning

## **Architects' And Engineers' Specifications**

The Illuminated Area of Rescue Sign(s) shall be Alpha Communications  $\$  / Tektone S1004 single-sided (or S1004/2 double-sided) or approved equal. The sign(s) shall 11.0" high x 22.0" wide x 2.75" deep. The sign(s) shall include area of rescue assistance messages and symbols in White on a contrasting Blue background illuminated by low-power Red LEDs. The sign(s) shall be equipped with two (2) movable emergency battery-powered back-up lights.

The sign(s) shall comply with ADA requirements. In addition, contractor shall observe all local and national electrical and building codes.

## \$1004 & \$1004/2 Illuminated Area of Rescue Signs

The SI004 and SI004/2 Illuminated Area of Rescue Signs provide indication for Area of Rescue locations. The signs comply with the Americans with Disabilities Act (ADA) requirements, and are intended to be used in conjunction with Alpha Communications  $^{\mathbb{N}}$  TekTone NC150R Area of Rescue Systems, AlphaRefuge  $^{\mathbb{N}}$  Systems (or equivalents systems by others).

The signs provide visual directions to areas where people who require assistance in evacuating a building can go to await assistance. The SI004 is a single-sided back-lit sign and the SI004/2 is a double-sided unit, having back-lit signs on both the front and the back.

#### **Features**

- Meets ADA requirements (check local codes for additional requirements)
- Text is White on a contrasting Blue background, and illuminated by low power, long lasting Red LEDs
- Each directional arrow (right and left) can be individually knocked out in the field
- Sign is equipped with two (2) movable batterypowered emergency backup lights
- Up to 90 minutes battery run-time

### **Specifications**

Dimensions:	Height: 11.0" (172mm) Width: 22.0" (712mm) Depth: 2.75" (108mm)
Power:	Standard 120 VAC input

### Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: AlphaCommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2016 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.