



SS911 Tamper-resistant Remote Station (RM5000EX / CB901EX Series)



Architects' And Engineers' Specifications

The remote station(s) shall be Alpha Communications® / Ring model **SS911** or approved equivalent. Remote(s) shall have clear two-way communications. Remote(s) shall feature a tamper-resistant design to protect the speaker, microphone, LED, call button, and circuitry from external abuse and the elements. Remote faceplate shall be made of high quality 11 gauge Stainless Steel, in a brushed finish.

Remote(s) flush mounts in a 3.50" deep three gang electrical box (our model **BBF910**) with four tamper resistant screws (not included), or can be surface mounted using a model **BBS910** surface back box. Remote is designed to work with the **RM5000EX** and/or **CB901EX** microprocessor intercom systems. When used as a elevator remote station, calling to the **AND16** series annunciator, each **SS911** requires the contractor to furnish and install a model **AN912** annunciator control module.

Contractor shall observe all local and national electrical and building codes.

SS911 Tamper-Resistant Remote Substation

The **SS911** is a tamper-resistant remote station designed to protect the speaker, microphone, LED, call button, and circuitry from external abuse and the elements. This remote station is ideally suited for use in elevator, correctional facilities, institutions, parking facilities and secured entrances. The **SS911** is designed to work with the **RM5000EX** and/or **CB901EX** microprocessor intercom systems.

The face plate is constructed of high quality 11 gauge Stainless Steel with a brushed finish. The weather-resistant 45 ohm speaker is physically protected by an offset baffle and the microphone is encased in a machined block to prevent tampering. For a wider viewing angle and considerable security, the LED is mounted behind .250" thick LUCITE. Heavy duty piezo call switches offer strength and reliability with no moving parts to wear out.

Remote(s) flush mounts in a 3.5" deep three gang electrical box (our model **BBF910**) with four tamper resistant screws (not included), or can be surface mounted using a model **BBS910** surface back box.

When used as a elevator remote station, calling to the **AND16** series annunciator, each **SS911** requires a model **AN912** annunciator control module.

Features

- Clear two-way communications
- Tamper-Resistant Stainless Steel
- Call button and L.E.D. Indicator
- Easy installation
- Simple home-run wiring

Specifications

Dimensions:	6.375" (162mm) W x 4.475" (114mm) H x 3.00" (77mm) D
Weight:	1.5 lbs
Finish:	Brushed finish
Material:	11 gauge Stainless Steel
Mounting:	<ul style="list-style-type: none"> • Surface Housing: BBS910 • Flush Mounting: BBF910 3.50" deep three gang electrical box with four tamper resistant screws (not included)

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
 TOLL-FREE: (800) 666-4800 • Web: AlphaCommunications.com • Email: info@alphacommunications.com

Copyright © 1998-2014 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice. [Next \(APS255\) >](#)