



ULT-P2LPR150 2 Megapixel IP Plug & Play Mini Bullet, 2.8-12mm, 150' IR Range, PoE/DC12V

2 Megapixel Plug & Play	2.8-12mm	License Plate Capture 100 MPH
H.264 / H.264+	True Day/Night	True WDR 140dB
EXIR 150' Range	Audio In/Out	IP67 Weatherproof
PoE/DC12V	ONVIF	SD Card Slot
Free App iOS & Android	FREE CMS	Free MAC Client

Features

- 2 Megapixel (1920x1080) Resolution
- 2.8-12mm Varifocal Lens
- Records license plates on vehicles going up to 100mph
- H.264/H.264+, MJPEG Compression
- True Day/Night
- True WDR 140dB
- 150' EXIR Range
- Audio Input/Output
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- SD Local Storage, 128GB
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC Client

Mounting Options



Ordering Information

ULT-P2LPR150: 2 Megapixel, 2.8-12mm

*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

Model Number	ULT-P2LPR150
Image Sensor	1/2.8" progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter time	1s ~ 1/100.000s
Lens	2.8-12mm @ F1.4 angle of view: 113°~33.8°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	140dB
Backlight compensation	Yes, zone configurable
Video compression	H.264 / H.264+ / MJPEG / MPEG4
H.264 compression profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
Max. image resolution	1920 x 1080
Frame rate	60Hz: 60fps (1920 x 1080), 60fps (1280 x 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
On board Storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Audio	1/1
Alarm	1/1
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC ± 10%, PoE (802.3at)
Power consumption	Max. 15W
Ingress protection	IP67
EXIR range	up to 150ft
Dimensions	100x103.9x311.8mm (3.93"x4.09"x12.28")
Weight	2000g (4.41 lbs)
Included Accessories	IUM-BRJB1 Junction Box #1