



ULT-C2TXIR 2 Megapixel/1080p TVI Outdoor Turret, WDR, 120' EXIR Range, 12VDC

2 Megapixel

True Day/Night

True WDR

EXIR
120' Range

UTC
Up The Cable Control

IP66
Weather Resistant

Operates to -40° F

DC12V

Features

- 2 Megapixel (1920 x 1080) Resolution
- True Day/Night
- 120' IR Range with EXIR Technology
- Up The Cable (UTC) Function
- IP66 Weather Resistant
- Withstand up to -40° Operation
- 12VDC Only Operation

Mounting Options

 IUM-TRJB1:
Turret Junction Box #1

 IUM-BRCM1*
Corner Mount #1

 IUM-BRPM1*
Pole Mount #1

Model Number	ULT-C2TXIR28
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	1/25 s to 1/50,000s
Lens (Angle of View)	2.8mm
Auto Iris	Yes
Angle Adjustment	Pan: 0 – 360°, Tilt: 0 – 75°, Rotation: 0 – 360°
Day & Night	IR Cut Filter with Auto Switch
Wide Dynamic Range	True WDR, 120dB
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 30fps
HD Video Output	1 HD-TV1 output up to 1200ft with RG59U 95%
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On / Off, maximum 2 zones
Motion Detection	On / Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Digital noise reduction, Digital zoom(62x)
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F)
Humidity	Humidity 90% or less (non-condensing)
Power Supply	12 VDC+10%
Power Consumption	Max. 3W
Housing	IP66
IR Range	Up to 120 ft
Communication	OSD (UTC Control) via DVR
Dimensions	φ4.33 x 3.67 in (109.9 x 93.2mm)
Weight	0.57lbs (258g)

Ordering Information

ULT-C2TXIR28: 2 Megapixel Turret, 2.8mm

*To use these mounts with the selected cameras drill the holes needed into the mount using the diagram included with the camera. InVid Tech, reserves the right to make changes to improve our products at any time without notice; we are not responsible for misprints.

2 MEGAPIXEL | 1080p