

BACKUP CAMERA SYSTEM TWO CAMERA SETUP WITH TRAILER TOW QUICK CONNECT RVS - 770614 - 213

REAR VIEW
SAFETY
REVERSE WITH CONFIDENCE™



This two camera backup camera system is perfect for the fifth wheel or travel trailer application where you want a backup camera on the back of the trailer and one reverse camera on the truck. The system is complete with a crystal clear 7" LED Digital Panel COLOR monitor display with mirror image capability and distance grid lines, 2 channels with automatic system switch, two (2) 130° CCD cameras with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The 5th wheel rear view back up camera system is completely weatherproof with an IP69K rating. The quick connect/disconnect is 66' to camera and 26' to the monitor. The system is strong and reliable, shock resistant with a 20G vibration rating (highest in the industry) and comes with a full year warranty. System can be upgraded to the Quad View Monitor where multiple cameras can be viewed simultaneously.

BACKUP CAMERA SYSTEM TWO CAMERA SETUP WITH TRAILER TOW QUICK CONNECT



RVS - 770614 - 213

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" LED DIGITAL PANEL MONITOR WITH REMOVABLE SUNSHADE
- 2.5 MM COLOR CCD CAMERA WITH A 130° VIEWING ANGLE
- 3 CHANNEL SYSTEM ALLOWING YOU TO CONNECT ADDITIONAL CAMERAS
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



MONITOR

MONITOR	7" LED DIGITAL PANEL
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT	16:09
CONTRAST RATIO	500:01:00
DISPLAY BRIGHTNESS	400CD/m ²
VIEWING ANGLE	U:50° D:60° L/R:70°
VIDEO INPUT	3 CHANNEL CVBS
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 9V-32V
POWER CONSUMPTION	5W
AUDIO OUTPUT	0.5W SPEAKER
OPERATING TEMPERATURE	-20°C ~ +70° C
STORAGE TEMPERATURE	-30°C ~ +85°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5.25" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.1926 (H) X 0.1710 (V)
ACTIVE AREA	154.08 (H) X 85.92 (V) MM
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 752 (H) X 582 (V) NTSC: 811 (H) X 507 (V)
LENS	F=2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX