

G-Series 4 Channel Backup Camera System

RVS-776718-4CH

REAR VIEW
SAFETY
A Safe Fleet Brand



Now you can finally see it all! This G-series backup camera has 4 channels, allowing you to connect and view 4 cameras. This system features the legendary G-Series Monitor and the 776 Camera which despite its small size is powerfully built to withstand all weather conditions.

The G-Series monitor replaces the existing rear view mirror for a clean look. Its screen is 4.3 inches wide and pushed to the left of the mirror to be more easily viewed by the driver. For an absolute perfect backing up experience, this monitor comes with adjustable grid lines, allowing you to adjust the grid lines to be completely accurate regardless of where you mount the camera.

The backup camera in this system is surface mounted and can fit almost any vehicle. This slick compact design makes the camera virtually invisible. The camera has an IP68 rating which makes it completely weatherproof and boasts excellent night vision. This system comes included with all parts necessary for installation.

**G-Series 4 Channel Backup
Camera System
RVS-776718-4CH**

- Mirror monitor with 4.3" display
- Distance grid lines for backup up reference
- 4 video inputs - connect up to 3 additional cameras
- Completely waterproof camera - IP68



MONITOR

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	12001X
VIEWING ANGLE	U&D: 100°, L&R: 120°
VIDEO INPUT	4 CHANNEL
VIDEO SOURCE	1VP-P, 750
WORKING VOLTAGE	DC 9V - 32V
OPERATING TEMPERATURE	-20°C ~ +75°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
VIBRATION RATING	5G
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX