

# G - SERIES BACKUP CAMERA SYSTEM WITH 5" ANDROID OPERATED DISPLAY

## RVS - 776718 - 5

REAR VIEW  
**SAFETY**

A Safe Fleet Brand



For a backup camera system which fits almost any vehicle and is virtually invisible, look no further than the G-Series Camera System. This system features the legendary G-Series Monitor and the 776 Camera which despite its small size is powerfully built to withstand all weather conditions.

The monitor runs off the Android operating system and allows connection to WiFi networks for full internet browsing. The Google Play store is also available from this monitor allowing you to download any app available on the Android market! It comes with 8GB of built-in storage and can handle microSD cards up to 32GB.

The backup camera is completely waterproof with an IP68 rating and boasts excellent night vision. The system includes all parts necessary for installation and a one year warranty.

# G - SERIES BACKUP CAMERA SYSTEM WITH 5" ANDROID OPERATED DISPLAY

## RVS - 776718 - 5

**REAR VIEW  
SAFETY**

A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- MONITOR RUNS OFF THE ANDROID OPERATING SYSTEM AND ALLOWS CONNECTION TO WIFI NETWORKS FOR FULL INTERNET BROWSING
- SUPER BRIGHT 5 INCH SCREEN
- COMES WITH 8GB OF BUILT-IN STORAGE AND CAN HANDLE MICROSD CARDS UP TO 32GB.
- CONNECTS TO THE GOOGLE PLAY STORE TO DOWNLOAD ANY APP ON ANDROID MARKET



### MONITOR

SCREEN SIZE	5"
DOT RESOLUTION	800 X 3 (RGB) X 480
DISPLAY FORMAT	16:9
DISPLAY CONTRAST	700:1
DISPLAY BRIGHTNESS	6501X
VIEWING ANGLE	U: 50° D: 70° L&R: 70°
TYPE	TFT LCD
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	8W
OPERATING TEMPERATURE	-20 °C ~ +75 °C
VIDEO SYSTEM	AUTO NTSC/PAL
WEIGHT	800G
IMPACT RATING	5G
SYNC SYSTEM	INTERNAL

### CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX