

G - SERIES BACKUP CAMERA SYSTEM WITH NAVIGATION AND BLUETOOTH RVS - 776718 - NAVBT

**REAR VIEW
SAFETY**
A Safe Fleet Brand



For a backup camera system which fits almost any vehicle and is virtually invisible, look no further than the G-Series Camera System. This system features the legendary G-Series Monitor and the 776 Camera which despite its small size is powerfully built to withstand all weather conditions.

This mirror monitor bundles a whole range of features into one unit. It acts as a rear view mirror, displays the backup camera, comes with complete GPS Navigation and has full Bluetooth capabilities. This monitor will direct you to your destination with the safety of a backup camera and the ease of hands free bluetooth.

The backup camera is completely waterproof with an IP68 rating and boasts excellent night vision. The system comes included with all parts necessary for installation and a one year warranty.

G - SERIES BACKUP CAMERA SYSTEM WITH NAVIGATION AND BLUETOOTH

RVS - 776718 - NAVBT

**REAR VIEW
SAFETY**
A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- COMPLETE GPS NAVIGATION AND HAS FULL BLUETOOTH CAPABILITIES
- SUPER BRIGHT 4.3" COLOR TFT DIGITAL DISPLAY
- MIRROR MOUNTED MONITOR ATTACHES TO WINDSHIELD, REPLACING EXISTING REAR VIEW MIRROR
- NIGHT VISION PROVIDES A GREAT PICTURE AT NIGHT USING VERY LITTLE AMBIANT LIGHT



MONITOR

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	12001X
VIEWING ANGLE	U&D: 100°, L&R: 120°
TYPE	TFT LCD
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	8W
OPERATING TEMPERATURE	-20°C ~ +75°C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
IMPACT RATING	5G
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V139
SENSOR FORMAT	728 (H) X 560 (V)
PICTURE ELEMENTS	307,200 PIXELS
NTSC OUTPUT	720 (H) X 480 (V)
PAL OUTPUT	720 (H) X 576 (V)
OPTICAL FORMAT	1/4 INCH
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TV LINES
LENS	2.1MM
VIEW ANGLE	170°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
NIGHT VISION	YES
USABLE ILLUMINATION	0.5 LUX
POWER SOURCE	DC 9V - 32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P 75 Ω
VIBRATION AND SHOCK RATING	10G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +80°C / RH 95% MAX