



VIS-P4DRIR

4 Megapixel IP Plug & Play, Outdoor Rugged Dome
Fixed Lens, 98' IR Range, SD Card Slot, PoE/DC12V

Features

- 4 Megapixel (2592 x 1520) Resolution
- Fixed Lens
- H.265/H.264/MJPEG Compression
- True Day/Night
- True WDR 120dB
- Smart Analytics
- Smart IR Range up to 98'
- SD Card Local Storage, 128GB
- Audio Input/Output
- IK10 Vandal Resistant
- IP67 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

| | |
|----------------------------|--|
| Model | VIS-P4DRIR |
| Camera | |
| Sensor | 1/3", 4 megapixel, progressive scan CMOS |
| Lens | 2.8 mm@F2.0 |
| Angle of View (H) | 101.8° |
| Shutter | Auto/Manual, 1/6~1/100000s |
| Min. Illumination | Colour: 0.02 Lux (F2.0, AGC ON) 0 Lux with IR |
| Day/Night | IR-cut filter with auto switch (ICR) |
| S/N | >55 dB |
| WDR | 120 dB |
| Video | |
| Max. Resolution | 2592 × 1520 |
| Video Compression | H.265, H.264, MJPEG |
| Frame Rate | 4MP (2592×1520): Max. 20 fps; 4MP (2560×1440): Max. 25 fps, 3MP (2048×1520): Max. 30 fps; 1080P (1920×1080): Max. 30 fps |
| Video Streaming | Triple |
| 9:16 Corridor Mode | Supported |
| ROI | Supported |
| Evaluative Metering | Supported |
| OSD | Up to 8 OSDs |
| Privacy Mask | Up to 8 areas |
| Smart | |
| Behavior Detection | Intrusion, crossing line, motion detection |
| Exception Detection | Audio detection |
| Intelligent Identification | Face detection, Defocus, Scene Change |
| Statistical Analysis | People counting |
| Audio | |
| Audio Compression | G.711 |
| Two-way audio | Supported |
| Storage | |
| Edge Storage | Micro SD, up to 128 GB |
| Network | |
| Protocols | L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x |
| Compatible Integration | ONVIF, API |
| Interface | |
| Audio I/O | Input: impedance 35 kΩ; amplitude 2 V (p-p) Output: impedance 600 Ω; amplitude 2 V (p-p) |
| Alarm I/O | 1/1 |
| Network | 10M/100M Base-TX Ethernet |
| General | |
| Power | 12 V DC, or PoE (IEEE802.3 af) Power consumption: Max 5.5W |
| Dimensions (Ø x H) | Φ108.5 x 81 mm (Ø4.28" x 3.2") |
| Weight | 0.45 kg (0.99 lb) |
| Working Environment | -35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 95% RH(non-condensing) |
| Ingress Protection | IP67 |
| Vandal Resistant | IK10 |
| Certifications | UL |

Ordering Information

VIS-P4DRIR: 4 Megapixel Rugged Dome, 2.8mm