



IMHD4K-32

32" Ultra High Definition 4K Monitor 3840 x 2160 Image
HDMI, DisplayPort

Features

- Superior Ultra High Definition 4K Image: 3840 x 2160
- Suitable for All Video Surveillance and Security applications
- Bright Illuminated Panel with 89° Viewing Angle
- Inputs: HDMI 2.0, HDMI 1.4 & DisplayPort
- Picture-by-Picture (PBP), Picture-in-Picture (PIP) & Anti-Burn-In
- 3D Combo Filter
- VESA Mount Compatible

| | |
|------------------------------|--|
| Model | IMHD4K-32 |
| Panel Type | 32" (16:9) LED Back-lit Monitor |
| Case Type | Metal |
| Max Resolution | 3840(H) x 2160(V) @ 60 Hz, downward compatible |
| Active Display Area | 708.48 (H) X 398.52 (V) |
| Pixel Pitch | 0.1845 (H) x 0.1845 (V) |
| Contrast Ratio (Max) | 3000:1 |
| Brightness (Max) | 300 cd/m ² |
| Response Time | 5ms |
| Viewing Angle | U/D: 89° / 89°, L /R: 89° / 89° |
| Display Colors | 1.07G |
| PC Compatible Frequency | 121.8-140KHz(H) / 47-63Hz(V) |
| Adjustable Color Temperature | 11000K / 9300K / 7500K / 6500K /USER |
| Video Compatibility | Multi-Standard for NTSC / PAL |
| Aspect Ratio | 16:09 |
| Speaker Multimedia Speakers | Right x 1 Left x 1, 2X5W |
| Sound Demodulation | Stereo. Audio |
| Mute | Yes |
| Operating Humidity | 20 % - 70 % |
| Operating Temperature | - 10 to 50 °C |
| Video Interface | HDMI 1.4 x 3, HDMI 2.0 x 1, DP 1.2 x 1 |
| Audio Interface | Audio Out x 1, |
| Safety & EMC Certification | CE / FCC / ROHS |
| Stand Type | Desktop |
| Color | Black |
| Button Position | Right Hand Side |
| Dimensions (H x W x D) | 28.79 x 17.02 x 1.92 inches (without mount) |
| POWER Voltage | AC100-230V |
| Power Consumption | ≤55W |

Ordering Information

IMHD4K-32: 32" 4K HDMI Monitor

