



6602WK

ICONA MONITOR, VIP KIT H264



Flush-mounted (on box art. 6117) or surface-mounted (with bracket art. 6620) colour monitor with 4.3" / 16:9 touch screen, full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro-SD card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard PoE systems. Dimensions 5.61"x5.79"x0.91". Compatible with H.264 video format.



6602WK

ICONA MONITOR, VIP KIT H264

MAIN SPECIFICATIONS

Audio system:	No
Audio/video system:	Yes
Flush-mounted:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Induction loop function:	Yes
Type of display:	LCD
Display size (inches):	4,3" 16:9
Touch screen display:	Yes
Display resolution (H x V):	480x272
B/W or colour display:	Color
Product colour:	White RAL9016
Sensitive Touch technology:	Yes
Total buttons:	9
Comaptibility with Video Entry Comelit App :	No

FUNCTIONS

Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Intercom function:	Yes
Privacy function:	Yes
Floor door call function:	Yes
Customisable ringtone:	Yes
Alarm function:	Yes
Privacy conversation function:	Yes
Key button function:	Yes
Automatic gain control (AGC):	Yes

HARDWARE SPECIFICATIONS

Removable terminals:	Yes
Ethernet ports:	Yes

SETTINGS

Loudspeaker volume control:	Yes
Ringtone volume control:	Yes
Display brightness control:	Yes



6602WK

ICONA MONITOR, VIP KIT H264

SETTINGS

Display contrast control:	Yes
Display colour control:	Yes

GENERAL DATA

Product height (inch):	5.61
Product width (inch):	5.79
Product depth (inches):	0.91

COMPATIBILITY

Vip system:	Yes
-------------	-----

TECHNICAL SPECIFICATIONS

Maximum current absorption (mA):	200
Support SD card (card not in equipment):	Yes
Operating temperature (°F):	23 ÷ 104
Video encoding:	H.264
Product weight (oz):	0
IP assignment:	Auto IP



6602WK

ICONA MONITOR, VIP KIT H264


ACCESSORIES



6612

DESK BASE FOR ICONA MONITOR

Angle-adjustable desk base, for desk conversion of the Icona monitor. Complete with 1 x 2 m cable fitted with RJ45 connector for connecting the monitor terminals to the clasp or to a residential series jack. Dimensions: 5.7"x7.4"x4.7".



6612A

DESK BASE FOR ICONA MONITOR



6617

Flush-mounted box for plasterboard. Icona

Flush-mount box allowing mounting of Icona series monitors on plasterboard and/or cement walls. Dimensions: 129x129x50 mm



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 5.4"x5.6"x0.5".



1214/2C

BRANCH TERMINAL FOR SIMPLEBUS COLOR SYSTEM

Line branch terminal. The terminal must be connected on the riser to be branched towards brackets or telephones.



6117

FLUSH-MOUNTED BOX FOR PLANUX, SMART, ICONA MONITORS

The accessory can be used for the tilt-adjustment fitting of art. 6122. Dimensions: 132X132X50 mm.



6602WK

ICONA MONITOR, VIP KIT H264



6118

RETROFIT BRACKETS FOR DRY WALL. PLANUX AND SMART MONITORS

Retrofit Mounting brackets for dry wall. For Planux and Smart monitors