



Summary

This MEGApix® IP camera provides 1080p, 2.1 megapixel resolution at real-time 30fps. It includes a 2.8mm fixed lens with image enhancement features such as 120db True WDR, Samrt IR™ and Smart DNR™, all in an IP66, IK10-rated vandal-resistant housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP 1/2.7" Image Sensor at Real-time 30fps
- 2.8mm Fixed Lens
- True Wide Dynamic Range (WDR)
- Dual Codecs (H.264, MJPEG) with Simultaneous Streaming •
- 50' Smart IR[™] with Intelligent Camera Sync
- Smart DNR[™] 3D Digital Noise Reduction
- True Day/Night Mechanical IR Cut Filter
- Programmable Privacy Zones
- Auto Gain Control (AGC)
- Backlight Compensation (BLC) •
- Auto White Balance (AWB)
- Motion Detection
- · Micro SD/SDHC/SDXC Class 10 Card Slot for Event and Continuous Recording(Card Not Included)
- · Web Server Built-in
- · PoE Class 2 / DC12V
- ONVIF Conformant, Profile S
- · IP66 Certified Weather and Tampering Resistant
- IK10-Rated Impact-Resistant
- 5 Year Warranty

Accessories (Optional)



DWC-V7WM

Wall Mount for V7



DWC-V7JUNC Junction Box for V7 Outdoor Dome Cameras Outdoor Dome Cameras DWC-V7CM Ceiling Mount for V7 Outdoor Dome Cameras









(T): www.digital-watchdog.com

Dimensions unit : Inch (mm)





4.1" (105mm)

Specifications

| IMAGE | 0.1110.1/0.78.01400 |
|---------------------------------------|--|
| Image Sensor | 2.1MP 1/2.7" CMOS |
| Effective Pixels | 1928(H) x 1088(V) |
| Minimum Scene Illumination | F2.0 (30IRE): 0.25 Lux (Color) |
| LENS | F2.0 (30IRE): 0.0 Lux (B&W) |
| Focal Length | 0.0mm F0.0 |
| 0 | 2.8mm, F2.0 |
| Lens Type IR Distance | Fixed Lens 50ft Range IR |
| Angle of View | 118° |
| OPERATIONAL | 110 |
| | Auto Manuel Auti Elistenian |
| Shutter Mode | Auto, Manual, Anti-Flickering |
| Shutter Speed | 1/15~1/32000 |
| Slow Shutter | Off, 2x, 3x, 5x, 6x, 7.5x, 10x |
| Smart DNR™ 3D Digital Noise Reduction | 0~11 |
| Auto Gain Control | Auto |
| Wide Dynamic Range (WDR) | Off, 2x |
| Wide Dynanmic Range dB | 120dB |
| Day and Night | Auto, Day (Color), Night (B/W) |
| Privacy Zones | 16 Programmable Privacy Zones |
| Alarm Notifications | Notifications Via E-mail, SD Card or FTP Server |
| Memory Slot | Micro SD / SDHC / SDXC. Card not Included |
| NETWORK | |
| LAN | 802.3 Compliance 10/100 LAN |
| Video Compression Type | H.264, MJPEG |
| Resolution | 1920x1080 ~ 480p(30fps) |
| Frame Rate | Up to 30fps at All Resolutions |
| Video Bitrate | 100kbps~10Mbps, Multi-rate for Preview and Recording |
| Bitrate Control | Multi Streaming CBR/VBR at H.264 (Controllable frame rate Bandwidth) |
| Streaming Capability | Dual-Stream at Different Rates and Resolutions |
| IP | IPv4 |
| Protocol | ONVIF, TCP/IP, UDP, RTP(UDP/TCP), RTSP, NTP, HTTP, HTTP SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2c/ v3(MIB-2) |
| Security | Password authentication, Multi-level user configuration HTTPS(SSL), IP filtering, 802.1x, Digest Authentication(ID/F |
| Maximum User Access | 10 Users |
| ONVIF Conformance | Yes |
| Web Viewer | OS: Windows [®] , MAC [®] OS, Linux [®] Browser: Internet Explorer, Chrome, Firefox, Safari |
| Video Management Software | DW Spectrum [®] IPVMS |
| ENVIRONMENTAL | |
| Operating Temperature | -4°F~122°F (-20°C~50°C) |
| Operating Humidity | Less than 90% (Non-Condensing) |
| IP Rating | IP66 Certified Weather and Tampering Resistant |
| IK Rating | IK10 Impact Resistant |
| Other Certifications | CE, FCC, RoHS |
| ELECTRICAL | 02,100,1010 |
| Power Requirement | (Adaptor not included) DC 12V, POE IEEE 802.3af Class2 |
| | PoE: Max. 5.4W |
| Power Consumption | DC 12V: 3.8W |
| MECHANICAL | |
| Material | Aluminum Die-casting |
| Dimensions | 4.13 x 2.38 in (105 x 60.7mm) |
| Weight | 0.95lbs (350g) |



Rev Date: 08/17

Copyright © Digital Watchdog. All rights reserved. Specifications and pricing are subject to change without notice.