



ALTV2416ULI, ALTV2416ULCBI UL Listed AC Isolated CCTV Power Supply

Rev. DSALTV2416ULI - B22F

Overview



- These Altronix Isolated CCTV Power Supplies provide 24VAC distributed via sixteen (16) isolated fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV2416ULI

- Sixteen (16) isolated fused protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV2416ULI3

ALTV2416ULI w/3-wire Line Cord.

ALTV2416ULCBI

- Sixteen (16) isolated Class 2 Rated PTC protected outputs.
- Outputs are rated @ 2.5 amp.

ALTV2416ULCBI3

ALTV2416ULCBI w/3-wire Line Cord.

Specifications

- | | |
|---|---|
| <ul style="list-style-type: none"> • Input 115VAC, 50/60 Hz, 6 amp. • 24VAC @ 25 amp (600VA) supply current. • Primary fuse rated @ 5 amp/250V. • Sixteen (16) 1.56 amp isolated outputs. • Illuminated power disconnect circuit breaker with manual reset. • Spare fuses provided (all models w/primary and/or secondary fuses). • Unit maintains camera synchronization. • Ease of installation saves time & eliminates costly labor. | <ul style="list-style-type: none"> • Product weight: <ul style="list-style-type: none"> - ALTV2416ULI: 23.3 lbs. - ALTV2416ULI3: 23.6 lbs. - ALTV2416ULCBI: 23.3 lbs. - ALTV2416ULCBI3: 23.6 lbs. • Shipping weight: <ul style="list-style-type: none"> - ALTV2416ULI: 24.3 lbs. - ALTV2416ULI3: 24.6 lbs. - ALTV2416ULCBI: 24.3 lbs. - ALTV2416ULCBI3: 24.6 lbs. |
|---|---|

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



European Conformity



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions

13"H x 13.5"W x 3.5"D

