



# **R2416ULI, R2416ULCBI UL Listed Isolated Rack Mount CCTV Power Supply**

Rev. DSR2416ULI - A31F

## **Overview**



- These Altronix Isolated Rack Mount CCTV Power Supplies provide 24VAC distributed via isolated fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

### ***R2416ULI***

- Sixteen (16) isolated fuse protected outputs.
- Outputs are rated @ 3.5 amp.

### ***R2416ULCBI***

- Sixteen (16) isolated Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

## **Specifications**

- 24VAC outputs.
- 25 amp (600VA) supply current.
- Sixteen (16) 1.6 amp isolated outputs.
- Input 115VAC 50/60Hz, 5.4 amp.
- Individually isolated outputs.
- Illuminated power disconnect circuit breaker with manual reset.
- Removable terminal blocks w/locking screw flanges.
- 3-wire grounded line cord.
- Individual power LEDs.
- Spare fuse(s) provided for all models.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- 2U rack mount chassis for use in standard EIA 19" rack.
- Product weight:
  - R2416ULI: 23.4 lbs.
  - R2416ULCBI: 23.3 lbs.
- Shipping weight:
  - R2416ULI: 24.4 lbs.
  - R2416ULCBI: 24.3 lbs.

## **Agency Approvals**



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

# Enclosure Dimensions

3.25"H x 19.125"W x 8.5"D

**View from back**

