



ELEV-P5BXIR

5 Megapixel IP Plug & Play, Outdoor Mini Bullet, 82' IR Range, WDR, PoE/DC12V

Features

- 5 Megapixel (2592x1944) Resolution
- Fixed Lens
- H.265/H.265+/H.264/H.264+ Compression
- True Day/Night
- True WDR 120dB
- Smart IR Range up to 82'
- TF Card Local Storage, 128GB
- Built-In Mic
- IP66 Weather Resistant
- 12VDC/PoE Operation
- ONVIF
- Smart Analytics
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform
- Free MAC client software available to manage your system from your Apple computer

Model	ELEV-P5BXIR28
Sensor+DSP	OS05A10+Hi3516D
Image Sensor	1/2.7" Progressive scan CMOS Sensor
Min. Illumination	0.01lux(Color), 0lux(IR on)
Lens Mount	M12
Lens	2.8 mm@F1.8: horizontal FOV: 102°, vertical FOV:74°
IR	14μX18pcs SMD LED
IR Range	82 ft
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	WDR
Digital noise reduction	2D/3D DNR
Compression Standard	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec profile	Base/Main/High profile
H.265 Codec profile	Main profile
Video Bit Rate	11 Kbps~9 Mbps
Triple Streams	Support
Image	
Max. Image Resolution	5MP(2592 × 1944)(default 15fps)
Frame Rate	50Hz:20fps 5MP(2592×1944), 25fps 4MP(2560×1440), 23fps 4MP(2304 × 1728), 25fps 3MP(2048×1536), 25fps 1080P(1920×1080), 25fps 960P(1280×960), 60Hz:20fps 5MP(2592×1944), 28fps 4MP(2560×1440), 26fps 4MP(2304×1728), 30fps 3MP(2048×1536), 30fps 1080P(1920 × 1080), 30fps 960P(1280 × 960), 30fps 720P(1280 × 720)
Sub Stream	50Hz:25fps 720P(1280×720), 25fps D1(704 × 576),25fps CIF(352 × 288), 60Hz:30fps 720P(1280 × 720), 30fps D1(704 × 480),30fps CIF(352×240)
Third Stream	50Hz:25fps CIF(352 × 288), 60Hz:30fps CIF(352 × 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	Support
HLC	Support
ROI	Support
Defog	Support
Network	
Network Storage	NAS(NFS/CIFS)
Protocols	"TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P,Bonjour"
Event	Motion Detection, Video Shelter (Tampering)
Smart Functions	Area Intrusion, Line crossing, Object Missing, Unattended Object, Fast Moving
System compatibility	Onvif 2.6,Profile S, CGI
Security	User authentication,IP address filtering,Video mask
Mobile Surveillance	iPhone, iPad,Android devices
Interface	
Communication interface	1 RJ45 10M / 100M Ethernet Port
General	
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 7W
Weather Proof	IP66
Vandalproof	Not support
Dimensions	ø 2.44" x 6.46"
Weight	.88 lbs (400g)

Ordering Information

ELEV-P5BXIR28: 5 Megapixel Bullet, 2.8mm