

Wide Dynamic Range Color Outdoor Dome Camera

HIGH RESOLUTION


INDOOR/OUTDOOR

WIDE DYNAMIC RANGE

WDRD3 2.8 - 12mm auto iris varifocal lens

Features

- Newest WDR technology allows for improved image quality in scenes consisting of both bright and dark areas
- Each pixel processed independently for improved image
- High quality image even in low light conditions
- Sharpest quality analog image
- Tamper resistant construction
- IP67 compliant
- Optional wall, ceiling and junction box adapters available
- 12VDC / 24VAC dual voltage operation
- 5 year warranty



Specifications

Image Sensor	1/3" Pixim® Seawolf DPS
Resolution.....	690 TV lines
Minimum Illumination.....	0.1 lux (sense up x64)
Effective Pixels	758 (H) x 540 (V)
Electronic Shutter	Max x64 (x2, x4, x8, x16, x32, x64)
Color Balance	Multiple selectable factory presets for most common situations Full manual override for special applications
Video Output.....	1.0Vp-p (sync. negative) termination 75 Ohm + 10%
TV System.....	NTSC
Scanning System.....	Progressive
Synchronization	Internal / External
S/N Ratio	More than 50dB (AGC off)
Dynamic Range.....	120dB (max)
AGC Control	0-50dB
Gamma Characteristic.....	0.45 NTSC
Power Consumption	190mA max.
Power Supply	12VDC / 24VAC (dual voltage) (power supply not included)
Operating Temperature.....	14° F - 122° F
Dimensions.....	3.76" (H) x 5.92" (D)
Weight	1.76 lbs.

No WDR



WDR



Dome Cameras - Wide Dynamic Range

Bullet, Board, Dome & Traditional versions of this camera are also available.



WDRB1
pg. 90



WDR700VF
pg. 113



CVC624WDR
pg. 63



WDR T6
pg. 108

Optional Accessories



PSW4 or PSW5
24VAC or 12VDC
Power Supply