

**DESCRIPTION:**


The IS-DVF-HID is a video door station for the IS system, with a built in HID® ProxPoint® Plus card reader.

The video door station can be connected via CAT-5e/CAT-6 wire to the following IS exchange units: IS-CCU, IS-SCU. Maximum distance from the door station to the exchange unit is 980'.

Wiring and power for the card reader are separate from the intercom wiring. The card reader is to be connected to a host controller of any type that is compatible with the HID® ProxPoint® Plus proximity card reader.

**FEATURES:**

- Video door station for IS System
- Stainless steel faceplate
- Directory strip
- HID® ProxPoint® Plus proximity card reader built in
- Tamper resistant screws



# IS-DVF-HID

Stainless Steel Flush Mount Video Door Station with HID® Proximity Reader

## FEATURE CALL-OUT DEFINITIONS:

- [1] Camera
- [2] Microphone
- [3] White LED illuminator
- [4] Speaker
- [5] Directory card
- [6] Call status indicator
- [7] Call button
- [8] HID Proximity reader

## SPECIFICATIONS:

- Power Source: 48VDC (supplied from CEU)
- Communication: Open voice hands-free
- Camera: 1/4" color CMOS
- Min. illumination: 5 Lux
- Wiring: CAT-5e or CAT-6
- Wiring distance: 980'
- Door release contact: 24V AC/DC, 500mA  
(N/O, COM, N/C)
- Operating Temp: 14° - 140°F (-10° - 60°C)
- Dimensions: 7" W x 12-3/8" H x 1-7/8" D

## FEATURE CALL-OUTS:

