


NOTE: UNLESS OTHERWISE SPECIFIED

1. BLANK PATCH PANEL:
 - A. MATERIAL: 16 GA CRS
 - B. SURFACE FINISH: BLACK POWDER COAT
2. 6-PORT HD BEZEL:
 - A. MATERIAL: ABS, UL 94V-0
3. CAT 6 COUPLER:
 - ELECTRICAL:
 - A. CURRENT RATING: 1.5 AMPS MAX
 - B. VOLTAGE RATING: 150 VOLTS ALTERNATING
 - C. DIELECTRIC WITHSTANDING VOLTAGE: 1000 VOLTS RMS, 60 HZ
 - D. INSULATION RESISTANCE: > 10 MOHMS
 - MECHANICAL:
 - A. MATING FORCE: 5 LBS MAX
 - B. UNMATING FORCE: 5 LBS MAX
 - C. PLUG RETENTION IN JACK: 20 LBS MIN
 - D. DURABILITY: 750 CYCLES
 - MATERIAL & FINISH:
 - A. HOUSING: ABS, UL 94V-0
 - B. COLOR: BLACK
 - C. CONTACT: PHOSPHOR BRONZE GOLD PLATING OVER 100 MICRO INCH NICKEL
 - D. GOLD PLATING: 1.27 MICRON/50 MICRO INCH MIN

FREQUENCY (MHz)	NEXT (dB)	RETURN LOSS (dB)	ACRF (dB)	INSERTION LOSS (dB)
10.00	56.6	19.0	43.3	6.3
100.00	39.9	12.0	23.3	21.3
200.00	34.8	9.0	17.2	31.5
250.00	33.1	8.0	15.3	35.9

PIN	PIN
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8

PATCH PANEL, CAT 6, FEED-THRU 48-P, 2RMS		 Premium Products Proven Performance Competitive Prices
ITEM NO. ICMP48CP6	REV. A	
DWG NO. PSMPP48CP6	PAGE NO. 2	

CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com