
8P4C Keyed Surface Mount Jack With Shorting Bar

PRODUCT SPECIFICA/TION



- A. Surface Mount Jack Cover, 1 pc
- B. Surface Mount Jack Base, 1 pc
- C. Double Sided Adhesive Pad, 1 pc
- E. #6 x 3/4" Pan Head, Sharp Point Tapping Screw, 2 pcs



8P4C Keyed Surface Mount Jack With Shorting Bar


Features and Benefits:


- Provides a clean modular surface mount outlet solution for voice connectivity applications
- Designed to support a multitude of high tech communication needs for residential or commercial applications
- Keyed RJ31X jack with shorting bar allows the alarm/security system to over ride line one
- Provided with traditional screw down terminals
- Multiple mounting options including adhesive backing and screws
- Rugged and durable construction
- Available in ivory and white
- UL listed

SURFACE MOUNT JACK, KEYED, 8P4C			
ITEM NO.	IC635DS4XX	REV. A	
DWG NO.	PS635DS400	PAGE NO. 1	



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com





WIRING DIAGRAM:		
POSITION	WIRE COLOR	
1	BLUE	
2		
3		
4	RED	
5	GREEN	
6		
7		
8	GRAY	

SHORTING BAR ON PINS
1 & 4 AND 5 & 8

NOTE: UNLESS OTHERWISE SPECIFIED


- 1. MATERIAL:
 - A. SURFACE MOUNT JACK HOUSING: ABS, UL94V-0
 - B. SPRING WIRE CONTACTS: PHOSPHOR BRONZE GOLD PLATING

OVER 100 MICRO INCH NICKEL

- C. GOLD PLATING: 1.27 MICRON/50 MICRO INCH MIN
- D. WIRE LEADS: 26 AWG STRANDED WIRE
- E. TERMINATION SCREWS: 15 LBS/INCH MIN TORQUE

ZINC CHROMATIC PLATED STEEL

- F. TERMINAL LUGS: BRASS
- 2. COLOR: XX: IV-IVORY & WH-WHITE
- 3. MECHANICAL:
 - A. TOTAL MATING FORCE: 500 GRAMS
 - B. RETENTION: 17 LBS BETWEEN JACK AND PLUG
 - C. CRIMP TENSILE STRENGTH: 4.0-500 LBS
- 4. ELECTRICAL:
 - A. CURRENT RATING: 1.5 AMP MAX
 - B. DIELECTRIC WITHSTANDING VOLTAGE: 1,000 VOLTS RMS, 60 HZ
 - C. CONTACT RESISTANCE < 20 MILLIOHMS
 - D. INSULATION RESISTANCE > 10 MEGAOHMS





SURFA	SURFACE MOUNT JACK, KEYED, 8P4C			
ITEM NO.	IC635DS4XX	REV. A		
DWG NO.	PS635DS400	PAGE NO. 2		



CUSTOMER CARE / TECHNICAL SUPPORT * CSR@ICC.COM / 888-ASK-4-ICC (275-4422) * 14700 Alondra Blvd., La Mirada, CA 90638 * www.icc.com