

FLEXIDOME IP indoor 4000

www.boschsecurity.com



BOSCH
Invented for life



HD Onvif



- ▶ Indoor IP dome camera with varifocal lens
- ▶ 720p resolution
- ▶ Regions of interest and E-PTZ
- ▶ Motion, tamper and audio detection
- ▶ IR version with 15 m (50 ft) viewing distance

The 720p indoor dome camera from Bosch is a professional surveillance camera that provides high quality HD images for demanding security and surveillance network requirements. This dome is a true day/night camera offering excellent performance day or night.

The camera is also available with a built-in active infrared illuminator that provides high performance in extreme low-light environments.

Functions

iDNR reduces bandwidth and storage requirements

The camera uses intelligent Dynamic Noise Reduction (iDNR) which actively analyzes the contents of a scene and reduces noise artifacts accordingly.

The low-noise image and the efficient H.264 compression technology provide clear images while reducing bandwidth and storage by up to 30% compared to other H.264 cameras. This results in reduced-bandwidth streams that still retain a high image quality and smooth motion. The camera provides the most usable image possible by cleverly optimizing the detail-to-bandwidth ratio.

Area-based encoding is another feature which reduces bandwidth. Compression parameters for up to eight user-definable regions can be set. This allows uninteresting regions to be highly compressed, leaving more bandwidth for important parts of the scene.

The average typical optimized bandwidth in kbits/s for various image rates is shown in the table:

| IPS | 720p | 480p |
|-----|------|------|
| 30 | 1200 | 600 |
| 15 | 955 | 478 |
| 12 | 877 | 438 |
| 5 | 568 | 284 |
| 2 | 245 | 122 |

Stylish indoor dome with varifocal lens

Ideal for indoor use, the stylish design is suitable for installations where appearance and flexible coverage are important. The 3 to 10 mm varifocal lens allows you to choose the coverage area to best suit your application. Mounting options are numerous, including surface, wall, and suspended-ceiling mounting.

Multiple streams

The innovative multi-streaming feature delivers various H.264 streams together with an M-JPEG stream. These streams facilitate bandwidth-efficient viewing and recording as well as integration with third-party video management systems.

Regions of interest and E-PTZ

Regions of Interest (ROI) can be user defined. The remote E-PTZ (Electronic Pan, Tilt and Zoom) controls allow you to select specific areas of the parent image. These regions produce separate streams for remote viewing and recording. These streams, together with the main stream, allow the operator to separately monitor the most interesting part of a scene while still retaining situational awareness.

Built-in microphone, two-way audio and audio alarm

The camera has a built-in microphone to allow operators to listen in on the monitored area. Two-way audio allows the operator to communicate with visitors or intruders via an external audio line input and output. Audio detection can be used to generate an alarm if needed.

Tamper and motion detection

A wide range of configuration options is available for alarms signaling camera tampering. A built-in algorithm for detecting movement in the video can also be used for alarm signaling.

Edge recording

The MicroSD card slot supports up to 2 TB of storage capacity. A microSD card can be used for local alarm recording. Pre-alarm recording in RAM reduces recording bandwidth on the network, or – if microSD card recording is used – extends the effective life of the storage medium.

Cloud-based services

The camera supports time-based or alarm-based JPEG posting to four different accounts. These accounts can address FTP servers or cloud-based storage facilities (for example, Dropbox). Video clips or JPEG images can also be exported to these accounts. Alarms can be set up to trigger an e-mail or SMS notification so you are always aware of abnormal events.

Easy installation

Power for the camera can be supplied via a Power-over-Ethernet compliant network cable connection. With this configuration, only a single cable connection is required to view, power, and control the camera. Using PoE makes installation easier and more cost-effective, as cameras do not require a local power source.

The camera can also be supplied with power from +12 VDC power supplies. To increase system reliability, the camera can be simultaneously connected to both PoE and +12 VDC supplies. Additionally, uninterruptible power supplies (UPS) can

be used, which will allow continuous operation, even during a power failure. For trouble free network cabling, the cameras support Auto-MDIX.

True day/night switching

The camera incorporates mechanical filter technology for vivid daytime color and exceptional night-time imaging while maintaining sharp focus under all lighting conditions.

Access security

Password protection with three levels and 802.1x authentication is supported. To secure Web browser access, use HTTPS with a SSL certificate stored in the camera. The video and audio communication channels can be independently AES encrypted with 128-bit keys by installing the optional encryption site license.

Complete viewing software

There are many ways to access the camera's features: using a web browser, with the Bosch Video Management System, with the Bosch Recording System, with the free-of-charge Bosch Video Client, or with the video security mobile App. The Bosch Video Client PC surveillance software offers a user-friendly interface to support easy installation and configuration. It also provides easy live viewing of multiple cameras, playback, forensic search and export.

Video security App

The Bosch video security mobile App has been developed to enable **Anywhere** access to HD surveillance images allowing you to view live images from any location. The App is designed to give you complete control of all your cameras, from panning and tilting to zoom and focus functions. It's like taking your control room with you. This App, together with the separately available Bosch transcoder, will allow you to fully utilize our dynamic transcoding features so you can play back images even over low-bandwidth connections.

System integration

The camera conforms to the ONVIF (Open Network Video Interface Forum) Profile S specification. This guarantees interoperability between network video products regardless of manufacturer. For trouble-free network cabling, the camera supports Auto-MDIX which allows the use of straight or cross-over cables. Third-party integrators can easily access the internal feature set of the camera for integration into large projects. Visit the Bosch Integration Partner Program (IPP) website (ipp.boschsecurity.com) for more information.

Certifications and approvals

| Standards | |
|-----------|------------------------|
| | IEC 62471 (IR version) |
| | EN 60950-1 |
| | UL 60950-1 |

| | |
|-------------------------------|-------------------------------------|
| | CAN/CSA-C22.2 NO. 60950-1-03 |
| | EN 50130-4 |
| | EN 50130-5 |
| | FCC Part15 Subpart B, Class B |
| | EMC directive 2004/108/EC |
| | EN 55022 class B |
| | EN 61000-3-2 |
| | EN 61000-3-3 |
| | EN 55024 |
| | AS/NZS CISPR 22 (equal to CISPR 22) |
| | ICES-003 Class B |
| | VCCI J55022 V2/V3 |
| | EN 50121-4 |
| ONVIF compliance | EN 50132-5-2; IEC 62676-2-3 |
| Product certifications | CE, FCC, UL, cUL, C-tick, CB, VCCI |

| Region | Certification |
|--------|---------------|
| Europe | CE |
| USA | UL |
| | FCC |
| Canada | CSA |

Technical specifications

| Power | |
|-------------------|--|
| Input voltage | +12 VDC or Power-over-Ethernet (48 VDC nominal) |
| Power consumption | 4.5 W max. 6.0 W max. (IR version) |
| PoE | IEEE 802.3af (802.3at Type 1) Power level: Class 1 (Class 2 for IR version) |
| Power supply | 100–240 VAC to +12 VDC power supply unit included |

Video

| | |
|---|--|
| Sensor type | 1/2.7-inch CMOS |
| Sensor pixels | 1280 x 720 |
| Sensitivity (3200 K, reflectivity 89%, 30IRE, F1.3) | 0.24 lx (color) 0.05 lx (mono) 0.0 lx (IR) |
| Dynamic range | 76 dB |
| True Day/Night | Auto, Color, Monochrome |
| Shutter speed | Automatic Electronic Shutter (AES) |

| | |
|-------------------|--|
| | Fixed (1/30 [1/25] to 1/15000) |
| Video resolution | 720p, 432p, 288p, 144p |
| Aspect ratio | 16:9 |
| Video compression | H.264 MP (Main Profile); M-JPEG |
| Max. frame rate | 30 ips (M-JPEG frame rate can vary depending on system loading) |
| Video Settings | Video watermarking, Alarm mode stamping, Image mirror, Image flip, Contrast, Saturation, Brightness, White balance, Sharpness level, Contrast enhancement, Backlight Compensation, Privacy Mask, Motion detection, Tamper alarm, Upright mode, Pixel counter |

| Night vision (IR version only) | |
|--------------------------------|--------------------------------------|
| Distance | 15 m (50 ft) |
| LED | 15 LED high efficiency array, 850 nm |

| Optical | |
|--------------------------|--|
| Lens type | Varifocal 3 to 10 mm, DC Iris F1.3 - 360 |
| Lens mount | Board mounted |
| Horizontal field of view | 36° - 117° |
| Vertical field of view | 20° - 61° |

| Input/output | |
|--|---|
| Analog video out (for installation only) | 2.5 mm jack (1 Vpp CVBS) |
| Alarm input | Short or DC 5V activation |
| Relay out | Input rating Maximum 1 A, 24 VAC/VDC |
| Audio input | Built-in microphone Line in jack connector |
| Audio output | Line out jack connector |

| Audio streaming | |
|-----------------------|---|
| Audio Streaming | Full duplex / half duplex |
| Signal-to-noise ratio | > 50 dB |
| Audio compression | AAC-LC, G.711, L16 (live and recording) |

| Local storage | |
|------------------|---|
| Internal RAM | 10 s pre-alarm recording |
| Memory card slot | Supports up to 32 GB microSDHC / 2 TB microSDXC card. (An SD card of Class 6 or higher is recommended for HD recording) |
| Recording | Continuous recording, ring recording, alarm/events/schedule recording |

| Software | |
|---------------------------------------|---|
| Unit Configuration | Via web browser or Configuration Manager |
| Firmware update | Remotely programmable |
| Software viewer | Bosch Video Client |
| Network | |
| Protocols | IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, Telnet, ARP, DHCP, SNMP (V1, MIB-II), 802.1x, DNS, DNSv6, DDNS, SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, Digest Authentication. |
| Encryption | TLS 1.0, SSL, DES, 3DES, AES (optional) |
| Ethernet | 10/100 Base-T, auto-sensing, half/full duplex |
| Ethernet connector | RJ45 |
| Connectivity | ONVIF Profile S, Auto-MDIX |
| Mechanical | |
| 3-axis adjustment (pan/tilt/rotation) | 355° / 148° / 355° 355° / 100° / 355° (IR version) |
| Dimensions | Diameter: 135 mm (5.32 in) Height: 102 mm (4 in) |
| Weight | 554 g (1.22 lb) approx. |
| Color | RAL 9004, RAL 9010 |
| Environmental | |
| Operating temperature | -20 °C to +50 °C (-4 °F to +122 °F) |
| Storage temperature | -20 °C to +70 °C (-4 °F to +158 °F) |
| Humidity | 20% to 90% relative humidity (non condensing) |

Ordering information

FLEXIDOME IP indoor 4000 HD

Professional IP dome camera for indoor surveillance. Varifocal 3 to 10 mm lens; PSU included; iDNR; ROI; day/night; H.264 quad-streaming; cloud services; motion/tamper/audio detection; 720p
Order number **NIN-40012-V3**

FLEXIDOME IP indoor 4000 IR

Professional IP dome camera for indoor HD surveillance. Varifocal 3 to 10 mm lens; PSU included; iDNR; ROI; day/night; H.264 quad-streaming; cloud services; motion/tamper/audio detection; 720p; Infrared
Order number **NII-40012-V3**

Accessories

VEZ-A2-WW Wall Mount

White

Order number **VEZ-A2-WW**

NDA-ADTI-DOME Dome Adapter Bracket

Order number **NDA-ADTI-DOME**

VDA-PMT-AODOME Outdoor Pipe Mount

Outdoor pipe mount

Order number **VDA-PMT-AODOME**

LTC 9213/01 Pole Mount Adapter

Flexible pole mount adapter for camera mounts. Max. 9 kg (20 lb); 3 to 15 inch diameter pole; stainless steel straps

Order number **LTC 9213/01**

NDA-FMT200-DOME Flush-mount Bracket

In-ceiling flush mounting kit.

Order number **NDA-FMT200-DOME**

Software Options

BVIP AES 128 Bit Encryption

Single installation licence for BVIP AES 128-bit encryption site. Enables encrypted communication between BVIP devices and management stations.

Order number **MVS-FENC-AES**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com