



VIS-P2PTZXIR30

2 Megapixel IP, Outdoor PTZ, 30x, 492' EXIR Range, D-WDR, 2-Way Audio, SD Card Slot, PoE/24VAC

Features

- 2 Megapixel (1920 x 1080) Resolution
- H.265/H.264/MJPEG Compression
- True Day/Night
- Smart Analytics
- ONVIF
- 30x Optical Zoom
- Auto-Tracking
- Digital WDR
- Smart EXIR Range up to 492'
- Audio Input/Output
- IP66 Weather Resistant
- Operates to -40° F
- Micro SD Card Local Storage, 128 GB
- 24V AC/DC, PoE (PSE Required, sold separately)
- Free iOS & Android Apps for Smart Phones & Tablets
- Free Central Management Software (CMS) to manage multiple units & sites from a single platform

IVM-CORNER1: Corner Mount

IVM-JB6: Junction Box

IVM-PARAPET: Parapet Mount

IVM-PTZPOLE: Pole Mount

IVM-PTZWALL1: Short Wall Mount

IVM-PTZWALL2: Long Wall Mount

Ordering Information

VIS-P2PTZXIR30: 2 Megapixel PTZ, 30x Zoom

Camera	VIS-P2PTZXIR30
Sensor	1/3", 2megapixel, progressive scan, CMOS
Lens	4.5 ~ 135 mm (30x optical zoom)
Angle of View (H)	62.9° (wide) ~ 2.3° (tele)
Shutter	Auto/Manual; shutter time: 1/6 s ~ 1/100000 s
Minimum Illumination	Colour: 0.03 lux (F1.6, AGC ON) 0 lux with IR
Iris	Auto/Manual; F1.6 ~ F4.4
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
WDR	Digital WDR
Video	
Max. Resolution	1920 × 1080
Video Compression	H.265, H.264,MJPEG
Frame Rate	1080P (1920*1080): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 30 fps
Video Streaming	Triple
HLC	Supported
Evaluative Metering	Supported
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
Digital Zoom	Supported
Smart	
Behavior Detection	Intrusion, crossing line, motion detection
Exception Detection	Audio detection
Intelligent Identification	Face detection
Statistical Analysis	People counting
Audio	
Audio Compression	G.711
Two-way audio	Supported
Storage	
Edge Storage	Micro SD, up to 128 GB
Network	
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x
Compatible Integration	ONVIF,API
Pan & Tilt	
Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 240°/s, Preset speed: 300°/s
Tilt Range	-15° ~ +90° (auto reverse)
Tilt Speed	0.1° ~ 160°/s, Preset speed: 240°/s
Number of Presets	256
Patrol	Up to 16 patrols, up to 32 presets per patrol Note: The total number of patrols and patterns is 16.
Pattern	Up to 16 patterns, with the total recording time not less 15 minutes per pattern
Interface	
Audio I/O	Audio cable Input: impedance 35 kΩ; amplitude 2 V (p-p) Output: impedance 600 Ω; amplitude 2 V (p-p)
Alarm I/O	1/ 1
Network	1RJ45 10M/100M Base-TX Ethernet
General	
Power	24 V AC, 24 V DC Power consumption: 9 ~ 42W
Dimensions(ØxH)	Ø227x359.4 mm (Ø8.9" x 14.2")
Weight	5.28 kg (11.6lb)
Working Environment	-40°C ~ +65°C (-40°F ~ 149°F), Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP66