



Multi-channel Power Supplies



- ▶ **Multi-channel 24 or 28 VAC power output supplies**
- ▶ **Available in 4, 8 and 16 channel versions**
- ▶ **Wall-mountable steel enclosure**
- ▶ **Surge protection**
- ▶ **Power Off/On Switch**
- ▶ **LED power indicator**
- ▶ **Easy to install**

The Multi-channel Power Supplies are designed to support multiple 24/28 VAC, 50/60 Hz camera installations. These models operate from a 120 VAC, 50/60 Hz or from a 230 VAC, 50 Hz power source. Housed in a steel cabinet, with knockouts included for ease of installation and cable management, all power supplies include channel overload protection and unit surge protection.

Each output can be selected as 24 or 28 VAC. The 28 VAC option is ideal for applications with cameras at the end of long cable runs where significant voltage drops can occur. The ability to select the voltage of each output individually provides a greatly enhanced flexibility to meet the requirements of any installation.

These power supplies are ideal for both fixed camera use and for PTZ camera applications.

System Overview

The **ALTV244UL** is a four-channel power supply for indoor camera applications. This power supply provides a total of 3.5 Amps (3.0 Amps at 28 VAC output), with each channel limited to a maximum output of 3.5 Amps. This model requires a 115 VAC, 50/60 Hz power source.

The **ALTV244220** is a four-channel power supply for indoor camera applications. This power supply provides a total of 3.5 Amps (3.0 Amps at 28 VAC output), with each channel limited to a maximum output of 3.5 Amps. This model requires a 230 VAC, 50 Hz power source.

The **ALTV248UL3** is an eight-channel power supply for indoor camera applications. This power supply provides a total of 3.5 Amps (3.0 Amps at 28 VAC output), with each channel limited to a maximum output of 3.5 Amps. This model requires a 115 VAC, 50/60 Hz power source.

The **ALTV2416ULX3** is a sixteen-channel power supply for indoor camera applications. This power supply provides a total of 7 Amps (6.0 Amps at 28 VAC output), with each channel limited to a maximum output of 3.5 Amps. This model requires a 115 VAC, 50/60 Hz power source.

The **WPTV244300UL** is a four-channel power supply for outdoor camera applications. The power supply includes three (3) Class 2 Rated PTC protected outputs, with each PTC output limited to a maximum output of 2.5 Amps. The three (3) PTC-protected outputs provide a total of 12.5 Amps (10.0 Amps at 28 VAC output). The power supply also includes one (1) fuse-protected output limited to 15 Amps. This model requires a 115 VAC, 50/60 Hz power source.

Certifications and Approvals

Electromagnetic Compatibility (EMC)	Complies with FCC Part 15 and ICES-003 regulations
Product Safety	Complies with UL (UL 2044), CSA Standards (CSA Standard C22.2 No. 1-98), and CE
RoHS Compliance	All models
Environmental	WPTV244300UL: NEMA 4X, IP65 rated

Technical Specifications

Models

ALT244UL	Four (4) camera outputs, indoor
ALT244220	Four (4) camera outputs, indoor
ALT248UL3	Eight (8) camera outputs, indoor
ALT2416ULX3	Sixteen (16) camera outputs, indoor
WPTV244300UL	Three (3) PTC-protected outputs plus one (1) fuse-protected output, outdoor

Recommended Use¹

<ul style="list-style-type: none"> VG4 AutoDomes Modular Camera Series 	100, 200, 300, and 500i Series analog and IP applications
<ul style="list-style-type: none"> AutoDome Easy IP Cameras 	All analog and IP applications
<ul style="list-style-type: none"> AutoDome Easy II Cameras 	All applications
<ul style="list-style-type: none"> Dinion Series 	All analog and IP applications
<ul style="list-style-type: none"> FlexiDome Series 	All analog and IP applications
<ul style="list-style-type: none"> Unity Series Prepackaged Cameras 	All analog and IP applications
<ul style="list-style-type: none"> Extreme Environment Cameas 	All analog and IP applications
<ul style="list-style-type: none"> Extreme Environment Infrared Cameras 	All analog, IP and Bullet camera applications
<ul style="list-style-type: none"> High-Speed Positioning System 	All applications

1. The current requirements of all cameras connected to a power supply must be within the maximum current capacity of the power supply.

Electrical

Voltage Input

ALT244UL, ALT248UL3, ALT2416ULX3	115 VAC ± 10%, 50/60 Hz, 0.9 A
WPTV244300UL	115 VAC ± 10%, 50/60 Hz, 2.7 A
ALT244220	230 VAC ± 10%, 50 Hz, 1.8 A

Voltage Output

ALT244UL, ALT244220, ALT248UL3, ALT2416ULX3, WPTV244300UL	24/28 VAC, unregulated
---	------------------------

Total Output Current

	At 24 VAC	At 28 VAC	Max. Per Channel
ALT244UL, ALT244220, ALT248UL3	3.5 A	3.0 A	3.5 A
ALT2416ULX3	7.0 A	6.0 A	3.5 A
WPTV244300UL			
<ul style="list-style-type: none"> PTC-protected 	2.5 A	2.5 A	2.5 A
<ul style="list-style-type: none"> Fuse-protected 	12.5 A	10 A	15 A

Max. Current Output per Channel	3.5 A
Fuse Ratings	3.5 A
Main Fuse Ratings	5.0 A

Maximum Power Draw	At 24 VAC	At 28 VAC
ALT244UL, ALT244220, ALT248UL3	84 W	72 W
ALT2416ULX3	168 W	144 W
WPTV244300UL		
<ul style="list-style-type: none"> PTC-protected 	60 W	70 W
<ul style="list-style-type: none"> Fuse-protected 	300 W	280 W

Controls and Indicators	AC Power LED and On/Off switch, inside cabinet
-------------------------	--

Connections

Main Input	Flying leads
Low-voltage Outputs	Screw terminals

Mechanical

Construction/Finish	Beige metal case
Cable Entry	Knockouts for conduits

Dimensions (H x W x D)

ALT244UL, ALT244220, ALT248UL3	215.9 x 190.5 x 88.9 mm (8.5 x 7.5 x 3.5 in.)
ALT2416ULX3	330.2 x 342.9 x 88.9 mm (13.0 x 13.5 x 3.5 in.)
WPTV244300UL	305 x 197 x 114.3 mm (12.0 x 7.75 x 4.5 in.)

Shipping Weight

ALT244UL, ALT244220	3.18 kg (7.0 lbs)
ALT248UL3	3.3 kg (7.3 lbs)
ALT2416ULX3	6.3 kg (13.9 lbs)
WPTV244300UL	7.94 kg (17.5 lbs)

Product Weight

ALT244UL, ALT244220	2.9 kg (6.4 lbs)
ALT248UL3	3.1 kg (6.8 lbs)

ALTV2416ULX3	5.9 kg (12.9 lbs)
WPTV244300UL	7.60 kg (16.75 lbs)

Environmental

Operating Temperature

- All Indoor Models 0°C to +50°C (32 to +122°F)
- WPTV244300UL -20°C to +50°C (-4°F to +122°F)

Storage Temperature, all models -40 to +65°C (-40 to +149°F)

Humidity 30% to 85% relative

Ordering Information

ALTV244UL 120 VAC Power Supply Four-channel, 120 VAC, 60 Hz, 84 VA out, wall mount, indoor	ALTV244UL
ALTV244220 230 VAC Power Supply Four-channel, 230 VAC, 50 Hz, 84 VA out, wall mount, indoor	ALTV244220
ALTV248UL3 8-channel Indoor Power Supply, 120 VAC Eight-channel, 120 VAC input, 24/28 VAC output, 3.5 A total output, indoor	ALTV248UL3
ALTV2416ULX3 16-channel Indoor Power Supply, 120 VAC Sixteen-channel, 120 VAC input, 24/28 VAC output, 7 A total output, indoor	ALTV2416ULX3
WPTV244300UL 4-channel Outdoor Power Supply, 120 VAC Four-channel, 120 VAC input, 24/28 VAC output, 12.5 A total output, outdoor	WPTV244300UL
WPTV244300220 4-channel Outdoor Power Supply, 220 VAC Four-channel, 220 VAC input, 24/28 VAC output, 12.5 A total output, outdoor	WPTV244300220

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6258 5511
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by