

## VIDEO DOOR ENTRY SYSTEMS & KITS IKALL

1/2 OVERVIEW



#### 1622VC





Module which allows modulation and transmission of the colour video signal on the riser. On input it has the composite video signal of a colour camera. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all SBTOP functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.



# VIDEO DOOR ENTRY SYSTEMS & KITS IKALL

### 1622VC

### IKALL COLOUR REMOTE CAMERA AUDIO MODULE SB2 COLOUR

MAIN FEATURES	
Audio/video system:	Yes
Audio/video system:	Yes
Clamps:	L L V+V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-25 ÷ 55

FUNCTIONS	
Key button function:	Yes

HARDWARE SPECIFICATIONS	
Visual signalling:	Yes
Acoustic signalling:	Yes
Speech synthesis:	Yes

SETTINGS	
Loudspeaker volume control:	Yes
Microphone volume control:	Yes

GENERAL DATA	
Product height (inch):	55
Product width (inch):	102
Product depth (inch):	38

COMPATIBILITY	
Simplebus Top audio/video system:	Yes

ELECTRICAL SPECIFICATIONS	
Door release (dry contact bridge):	Yes
Door release (direct current output):	Yes