



1998A

PORTER SWITCHBOARD FOR SIMPLEBUS SYSTEM



Desk mounted porter switchboard with 32 character alphanumeric digital keypad. Allows the user code and name to be displayed, keeping the unanswered calls stored in the memory. Day/Night mode and intercom service. It also allows call transmission with indirect codes, management of alarm indications from internal devices. Can be used as a main or secondary switchboard. Up to 1000 names can be stored. 24VAC power supply from part. 1195. Compatible with all Simplebus systems. Dimensions: 158x223x35 mm.



1998A

PORTER SWITCHBOARD FOR SIMPLEBUS SYSTEM

MAIN FEATURES

Product height (inch):	9.06
Product width (inch):	6.3
Product depth (inch):	3.94
Operating temperature (°F):	23 ÷ 104
Maximum current absorption (mA):	200

SOFTWARE/FIRMWARE SPECIFICATIONS

Number of user codes:	1500
No. of storable users:	1500

FUNCTIONS

Alarm function:	Yes
Actuator control function:	Yes
Intercom function:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS

Customisable housing:	No
Sensitive Touch technology:	No

GENERAL DATA

Type of finish:	Plastic
Product colour:	White

COMPATIBILITY

Simplebus Top audio/video system:	Yes
Simplebus 1 audio system:	Yes

MOUNTING/INSTALLATION

Desk base-mounted:	Yes
--------------------	-----

CONNECTIVITY

Type of connections/ports:	RS232
RS232 ports:	1